

## R282-G30

Intel Xeon Rack Server - 2U 12-Bay GPU & NVMe sku



### Features

- Supports up to 3 x double slot GPU cards
- 3rd Gen. Intel® Xeon® Scalable Processors
- 8-Channel RDIMM/LRDIMM DDR4 per processor, 32 x DIMMs
- Dual ROM technology supported
- 2 x 1Gb/s LAN ports (Intel® I350-AM2)
- 1 x Dedicated management port
- 8 x 3.5" SATA hot-swappable HDD/SSD bays
- 4 x 3.5" SATA/NVMe hot-swappable HDD/SSD bays
- 5 x PCIe Gen4 x16 expansion slots
- 1 x OCP 3.0 Gen4 x16 mezzanine slot
- 1 x OCP 2.0 Gen3 x8 mezzanine slot
- 2400W (240V) 80 PLUS Platinum redundant power supply

### Specification

<b>Dimensions</b>	2U (438 x 43.5 x 730 mm)	<b>Front I/O</b>	2 x USB 3.0
<b>Motherboard</b>	MR92-FS1	<b>Rear I/O</b>	2 x USB 3.0, 1 x VGA, 2 x RJ45, 1 x MLAN
<b>CPU</b>	3rd Gen Intel® Xeon® Scalable Processors Intel® Xeon® Platinum Processor, Intel® Xeon® Gold Processor, Intel® Xeon® Silver Processor 10nm technology, CPU TDP up to 270W 2 x LGA 4189 sockets (Socket P+)	<b>Backplane I/O</b>	9CBP20C5NR-00: 8 x SATA/SAS and 4 x SATA/NVMe ports Speed and bandwidth: SATA 6Gb/s or SAS 12Gb/s or PCIe Gen4 x4 per port
<b>Chipset</b>	Intel® C621A Express Chipset	<b>TPM</b>	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
<b>Memory</b>	8-Channel DDR4 memory, 32 x DIMM slots RDIMM modules up to 64GB supported LRDIMM modules up to 128GB supported 3DS RDIMM/LRDIMM modules up to 256GB supported 1.2V modules: 3200/2933/2666 MHz	<b>Power Supply</b>	1+1 2400W (240V) 80 PLUS Platinum redundant power supply
<b>LAN</b>	2 x 1GbE LAN ports (1 x Intel® I350-AM2) 1 x 10/100/1000 management LAN	<b>System Management</b>	Aspeed® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
<b>Video</b>	Integrated in Aspeed® AST2600 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp, DDR4 SDRAM	<b>OS Compatibility</b>	Windows Server 2016 / 2019 RHEL 8.3 (x64) or later SLES 12 SP5 (x64) / 15 SP2 (x64) or later Ubuntu 18.04.5 LTS (x64) / 20.04 LTS (x64) or later VMware ESXi 6.7 Update3 P03 / 7.0 Update1 or later Citrix Hypervisor 8.2.0 or later
<b>Storage</b>	8 x 3.5"/2.5" SATA/SAS hot-swap HDD/SSD bays 4 x 3.5"/2.5" SATA/Gen4 NVMe hot-swap HDD/SSD bays SAS card is required for SAS devices support	<b>System Fans</b>	4 x 80x80x38mm (16'300rpm)
<b>RAID</b>	Intel® SATA RAID 0, 1, 10, 5 Intel® Virtual RAID On CPU (VROC) RAID 0, 1, 10, 5 Note: VROC module is compatible for Intel® SSD only	<b>Operating Properties</b>	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
<b>Expansion Slots</b>	5 x PCIe x16 slot (Gen4 x16), FHFL 1 x OCP 3.0 mezzanine slot (Gen4 x16) - Supported NCSI function 1 x OCP 2.0 mezzanine slot (Gen3 x8) - Supported NCSI function	<b>Packaging Content</b>	1 x R282-G30, 2 x CPU heatsinks 1 x Rail kit, 1 x VROC module
		<b>Reference Numbers</b>	Barebone package: 6NR282G30MR-00 - Motherboard: 9MR92FS1NR-00 - Rail kit: 25HB2-3A0202-K0R - CPU heatsink: 25ST1-343102-M1R

\* All specifications are subject to change without notice. Please visit our website for the latest information.

\* Intel, the Intel logo, the Intel Inside logo, Xeon, and Optane are trademarks of Intel Corporation or its subsidiaries.

\* NVIDIA, the NVIDIA logo are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and/or other countries.

