


## R282-Z96

Rack Server - 2U DP 12-Bay GPU & NVMe sku



### Features

- Supports up to 3 x double slot GPU cards
- NVIDIA-Certified system for scalability, functionality, security, and performance
- Dual AMD EPYC™ 7003 Series processors
- 8-Channel RDIMM/LRDIMM DDR4 per processor, 32 x DIMMs
- 2 x 1Gb/s LAN ports
- 8 x 3.5" SATA hot-swappable HDD/SSD bays
- 4 x 3.5" SATA/NVMe hot-swappable HDD/SSD bays
- Ultra-Fast M.2 with PCIe Gen4 x4 interface
- 4 x PCIe Gen4 x16 expansion slots
- 1 x OCP 3.0 Gen4 x16 mezzanine slot
- 1 x OCP 2.0 Gen3 x8 mezzanine slot
- 1+1 2000W 80 PLUS Platinum redundant power supply

### Specification

<b>Dimensions</b>	2U (W438 x H87 x D730 mm)	<b>Backplane I/O</b>	9CBP20C5NR-00: 8 x SATA/SAS and 4 x SATA/NVMe ports
<b>Motherboard</b>	MZ92-FS0 Rev. 3.0	<b>TPM</b>	1 x TPM header with SPI interface, optional TPM2.0 kit: CTM010
<b>CPU</b>	AMD EPYC™ 7003 Series processors Dual processors, 7nm, Socket SP3 Up to 64-core, 128 threads per processor TDP up to 225W, cTDP up to 280W, Fully support 280W Compatible with AMD EPYC™ 7002 Series processors	<b>Power Supply</b>	2 x 2000W 80 PLUS Platinum redundant power supply AC Input: 100-240V
<b>Chipset</b>	System on Chip	<b>System Management</b>	Aspeed® AST2500 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
<b>Memory</b>	8-Channel DDR4 memory, 32 x DIMM slots RDIMM/LRDIMM modules up to 128GB supported Memory speed: Up to 3200 MHz	<b>OS Compatibility</b>	Windows Server 2016 / 2019 RHEL 8.3 (x64) or later SLES 12 SP5 (x64) / 15 SP2 (x64) or later Ubuntu 18.04.5 LTS (x64) / 20.04 LTS (x64) or later VMware ESXi 6.7 Update3 P03 / 7.0 Update1 or later Citrix Hypervisor 8.2.0 or later
<b>LAN</b>	2 x 1Gb/s LAN ports (Intel® I350-AM2) 1 x 10/100/1000 management LAN	<b>System Fans</b>	4 x 80x80x38mm (16,300rpm)
<b>Video</b>	Integrated in Aspeed® AST2500 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp	<b>Operating Properties</b>	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing) Ambient temperature limited to 30°C if using 280W CPU
<b>Storage</b>	8 x 3.5"/2.5" SATA/SAS hot-swap HDD/SSD bays 4 x 3.5"/2.5" SATA/Gen4 NVMe hot-swap HDD/SSD bays SAS card is required for SAS devices support	<b>Packaging Dimensions</b>	982 x 588 x 268mm
<b>RAID</b>	N/A	<b>Packaging Content</b>	1 x R282-Z96 system 2 x CPU heatsinks 1 x Rail kit
<b>Expansion Slots</b>	4 x PCIe x16 slots (Gen4 x16), FHFL 1 x OCP 3.0 mezzanine slot (Gen4 x16) 1 x OCP 2.0 mezzanine slot (Gen3 x8 ) 1 x M.2 slot (Gen4 x4)	<b>Reference Numbers</b>	Barebone package: 6NR282Z96MR-00 Rev. A00 - Motherboard: 9MZ92FS0NR-00 Rev. 3.0 - Rail kit: 25HB2-3A0202-K0R - CPU heatsink: 25ST1-44320G-A0R - Power supply: 25EP0-22000A-L0S
<b>Front I/O</b>	2 x USB 3.0		
<b>Rear I/O</b>	2 x USB 3.0, 1 x VGA, 2 x RJ45, 1 x MLAN		



Learn more about GIGABYTE server solutions, visit [www.gigabyte.com/Enterprise](http://www.gigabyte.com/Enterprise)

\* All specifications are subject to change without notice. Please visit our website for the latest information.

\* AMD, and the AMD Arrow logo, AMD EPYC and combinations thereof are trademarks of Advanced Micro Devices, Inc.

\* All other brands, logos and names are property of their respective owners.

© 2021 GIGABYTE Technology Co., Ltd. All rights reserved.