

R283-S90-AAJ3

Rack Server - 2U DP 12+2-Bay NVMe/SATA/SAS



Key Features

- Dual 5th/4th Gen Intel® Xeon® Scalable Processors
- Dual Intel® Xeon® CPU Max Series
- 8-Channel RDIMM DDR5 per processor, 32 x DIMMs
- Dual ROM Architecture supported
- 2 x 1Gb/s LAN ports via Intel® I350-AM2
- 12 x 3.5"/2.5" Gen4 NVMe/SATA/SAS hot-swappable bays
- 2 x 2.5" SATA/SAS hot-swappable bays on the rear side
- 5 x FHHL PCIe Gen5 x16 slots
- 2 x LP PCIe Gen5 x8 slots
- 2 x OCP 3.0 Gen5 x16 slots
- Compatible with SupremeRAID™ by Graid Technology
- 1+1 2000W 80 PLUS Platinum redundant power supplies

Specification

Dimensions	2U (W438 x H87.5 x D815 mm)	I/O Ports	Front: 2 x USB 3.2 Gen1 Rear: 2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x RJ45, 1 x MLAN Internal: 1 x TPM header, 1 x VROC connector
Motherboard	MS93-FS0	Backplane Board	Front - CBP20C5: PCIe Gen4 x4 or SATA 6Gb/s or SAS 12Gb/s Rear - CBP2022: SATA 6Gb/s or SAS 12Gb/s
CPU	5th Generation Intel® Xeon® Scalable Processors 4th Generation Intel® Xeon® Scalable Processors Intel® Xeon® CPU Max Series Dual processor, TDP up to 350W	TPM	1 x TPM header with SPI interface (Optional TPM2.0 kit: CTM010)
Socket	2 x LGA 4677 (Socket E)	Power Supply	1+1 2000W 80 PLUS Platinum redundant power supplies AC Input: 100-240V
Chipset	Intel® C741 Chipset	System Management	ASPEED® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
Memory	8-Channel DDR5 memory per processor, 32 x DIMM slots RDIMM up to 96GB supported 3DS RDIMM up to 256GB supported Memory speed: Up to 5600 MHz (1DPC), 4400 MHz (2DPC)	OS Compatibility	Windows Server 2019 / 2022 RHEL 8.6 / 8.7 / 8.8 / 8.9 / 9.0 / 9.1 / 9.2 / 9.3 (x64) SLES 15 SP4 / 15 SP5 (x64) Ubuntu 22.04 LTS / 22.04.1 / 22.04.2 / 22.04.3 LTS (x64) VMware ESXi 7.0 Update 3o / 8.0 Update 1 / 8.0 Update 2 Citrix Hypervisor 8.2 LTSR CU1
LAN	2 x 1Gb/s LAN ports (1 x Intel® I350-AM2) Supported NCSI function 1 x 10/100/1000 management LAN	System Fans	4 x 80x80x38mm (18,300rpm)
Video	ASPEED® AST2600 Integrated 2D Graphic Adapter	Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
Storage	Front: 12 x 3.5"/2.5" Gen4 NVMe/SATA/SAS hot-swappable bays Rear: 2 x 2.5" SATA/SAS hot-swappable bays SAS card is required for SAS devices support	Packaging Content	1 x R283-S90-AAE3, 2 x CPU heatsinks, 6 x Carrier clips, 1 x Mini-DP to D-Sub cable, 1 x -Section Rail kit
RAID	Intel® SATA RAID 0/1/10/5 Optional compatible RAID Cards: NVMe RAID Cards with SupremeRAID™ by Graid Technology RAID Card models: SR-1000-ED12, support RAID 0/1/5/6/10	Part Numbers	Barebone package (5th/4th Gen): 6NR283S90DR000ABE3* Barebone package (4th Gen): 6NR283S90DR000AAE3* - 2-Section Rail kit (CMA not supported): 25HB2-3A0206-K0R - CPU heatsink: 25ST1-323208-A0R - Power supply: 25EP0-22000A-L0S
Expansion Slots	5 x PCIe Gen5 x16 FHHL slots 2 x PCIe Gen5 x8 LP slots 2 x OCP 3.0 Gen5 x16 slots - Supporte NCSI function		



Learn more about GIGABYTE server at <https://www.gigabyte.com/Enterprise>

Designed by



* All specifications are subject to change without notice. Please visit our website for the latest information.
* Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.
* All other brands, logos and names are property of their respective owners.

© 2023 Giga Computing Technology Co., Ltd. All rights reserved.