

R283-S91-AAJ1

2U DP 12+2-Bay NVMe/SATA/SAS Rack Server



Features

- 4th Gen Intel® Xeon® Scalable Processors
- Intel® Xeon® CPU Max Series
- Dual processors, LGA4677
- 8-Channel RDIMM DDR5 per processor, 32 x DIMMs
- Supports Intel® Optane™ Persistent Memory 300 series
- Dual ROM Architecture supported
- 2 x 1Gb/s LAN port (Intel® I350-AM2)
- 1 x Dedicated management port
- 4 x NVMe/SATA/SAS + 8 x SATA/SAS 3.5/2.5" hot-swap bays
- 2 x 2.5" SATA hot-swappable bays on rear side
- Onboard 12Gb/s SAS expander
- 6 x FHHL PCIe Gen5 x16 expansion slots
- 2 x LP PCIe Gen5 x8 expansion slots
- 2 x OCP 3.0 Gen5 x16 mezzanine slots
- Dual 2000W 80 PLUS Titanium redundant power supply

Specification

Dimensions	2U (W438 x H87.5 x D815 mm)	Front I/O	2 x USB 3.2 Gen1
Motherboard	MS93-FS0	Rear I/O	2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x RJ45, 1 x MLAN
CPU	4th Gen Intel® Xeon® Scalable Processors Intel® Xeon® CPU Max Series Intel® Xeon® Platinum Processor, Intel® Xeon® Gold Processor, Intel® Xeon® Silver Processor CPU TDP up to 350W	Backplane I/O	PCIe Gen4 x4 or SATA 6Gb/s or SAS 12Gb/s on front side SATA 6Gb/s or SAS 12Gb/s on rear side
Socket	2 x LGA 4677 (Socket E)	TPM	1 x TPM header with SPI interface (Optional TPM2.0 kit: CTM010)
Chipset	Intel® C741 Chipset	Power Supply	Dual 2000W 80 PLUS Titanium redundant power supply AC Input: 100-240V
Memory	8-Channel DDR5 memory per processor, 32 x DIMM slots RDIMM modules up to 128GB supported 3DS RDIMM modules up to 256GB supported Memory speed: Up to 4800 MHz (1DPC), 4400 MHz (2DPC)	System Management	Aspeed® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
LAN	2 x 1Gb/s LAN ports (1 x Intel® I350-AM2) Supported NCSI function 1 x 10/100/1000 management LAN	OS Compatibility	Windows Server 2019 / 2011 RHEL 8.4 / 8.5 / 8.6 / 8.7 / 9.0 / 9.1 (x64) SLES 15 SP3 / 15 SP4 (x64) Ubuntu 22.04 LTS / 22.04.1 LTS (x64) VMware ESXi 7.0 Update 3i / 8.0
Video	Integrated in Aspeed AST2600 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp, DDR4 SDRAM	System Fans	4 x 80x80x38mm (18,300rpm)
Storage	4 x 3.5/2.5" Gen4 NVMe/SATA/SAS hot-swappable bays 8 x 3.5/2.5" SATA/SAS hot-swappable bays 2 x 2.5" SATA/SAS hot-swappable bays on rear side Broadcom SAS35x24R expander SAS card is required to enable SATA/SAS drives	Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
RAID	Intel® SATA RAID 0/1/10/5	Packaging Content	1 x R283-S91, 2 x CPU heatsinks, 1 x Mini-DP to D-Sub cable, 6 x Carrier clips, 1 x Rail kit
Expansion Slots	6 x PCIe Gen5 x16 FHHL slots 2 x PCIe Gen5 x8 LP slots 2 x OCP 3.0 Gen5 x16 slots - Supporte NCSI function	Part Numbers	Barebone package: 6NR283S91DR000AAJ1* - Motherboard: 9AS93FS0UR-000 - Rail kit: 25HB2-3A0206-K0R - CPU heatsink: 25ST1-323208-A0R - Mini-DP to D-Sub cable: 25CRN-200801-K1R - Power supply: 25EP0-22000L-G1S



Learn more about GIGABYTE server solutions, visit www.gigabyte.com/Enterprise

* All specifications are subject to change without notice. Please visit our website for the latest information.

* Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.

* All other brands, logos and names are property of their respective owners.

© 2023 Giga Computing Technology Co., Ltd. All rights reserved.