

## T025-S11

ORv3 Compute Node - 20U 2Nodes




### Features

- 4th Gen Intel® Xeon® Scalable Processors
- Intel® Xeon® CPU Max Series
- Single processor, LGA 4677
- 8-Channel RDIMM DDR5, 8 x DIMMs
- Dual ROM Architecture
- 1 x dedicated management port
- 10 x E1.S NVMe hot-swappable bays
- 1 x M.2 slot with SATA interface
- 2 x FHHL PCIe Gen5 x16 slots on bottom side
- 1 x LP PCIe Gen5 x8 slot on bottom side
- 48V DC Bus Bar power solution


### GIGABYTE OCP ORV3 Compliant Solutions

GIGABYTE is an active member of the OCP, regularly attending the OCP's annual summits and continuously designing and releasing new compute, storage and GPU server hardware based on the OCP Open Rack Standard specifications and providing the best performing mezzanine cards for your OCP solution. GIGABYTE's latest OCP server product line is based on OCP Open Rack V3 specification. The products are designed for a 21" OCP rack and feature a separate PSU system, with power supplied to each server node by a bus-bar system running along the rear of the rack.

Compute Node



GPU Server



JBOD

OCP 21" Rack



### GIGABYTE OCP ORV3 Compliant Solutions Advantages

#### Efficient Rack Density

- Optimal design (20U 2nodes / 20U 3nodes) - balanced consideration between density and power consumption.

#### Thermal Optimization

- Best thermal consideration to develop Rack and Nodes based on Cold Aisle/Hot Aisle concept.
- Reduce power consumption of cooling.

#### Greater Power Efficiency

- Low PUE helps reduce data center operating expense.
- Central power shelf design to enhance power efficiency and optimize power consumption.

#### Easy Maintenance

- Easier maintenance in front cold aisle instead of hot aisle.
- Tool-less design for easy replacement and repair.
- Less PSU quantities in whole rack to minimize maintenance efforts.

#### Higher MTBF

- Centralizing power supplies and removing unnecessary components to enhance MTBF (Mean Time Between Failures).
- Avoids system downtime caused by component failure and minimizes maintenance efforts.

## The Future of Open Source Ecosystem

The Open Compute Project (OCP) is a collaborative community focused on redesigning hardware technology to efficiently support the growing demands on compute infrastructure. In 2011, the OCP Foundation was initiated with a mission to apply the benefits of open source and open collaboration to hardware and rapidly increase the pace of innovation. Its collaboration model is now being widely applied in fields like data centers, telecom industry, and edge infrastructure.



## Flexible Node Configuration

GIGABYTE's OCP Open Rack Version 3 compliant solutions maintain the cost-efficient designs created in version 2, yet these new solutions provide even more power to each node. GIGABYTE TO23-BT0, a 2OU node tray, supports three nodes and up to six CPUs in a single tray. And a similar node tray, TO25-BT0, is designed for more PCIe expansion slots with each tray supporting up to four dual-slot GPUs or eight full-height full-length single slot cards for growing HPC and AI needs in data centers.



## Specification

<b>Dimensions</b>	2OU 2-Node (W262.7 x H90 x D740 mm)	<b>Front I/O</b>	1 x USB 3.2 Gen1 Type-C 1 x Mini-DP 1 x MLAN 1 x ID LED 1 x ID button with LED 1 x Power button with LED 1 x System status LED
<b>Open Rack Version</b>	ORv3	<b>TPM</b>	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
<b>Motherboard</b>	MS13-HD0	<b>System Management</b>	Aspeed® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP X Solution Web interface)
<b>CPU</b>	4th Generation Intel® Xeon® Scalable Processors Intel® Xeon® CPU Max Series Single processor, CPU TDP up to 350W	<b>Packaging Content</b>	1 x TO25-S11, 1 x CPU heatsink, 3 x Carrier clips
<b>Socket</b>	1 x LGA 4677 (Socket E)	<b>OS Compatibility</b>	Windows Server 2019 / 2022 RHEL 8.6 / 8.7 / 9.0 / 9.1 / 9.2 (x64) SLES 15 SP4 Ubuntu 22.04 LTS / 22.04.1 LTS / 22.04.2 LTS (x64) VMware ESXi 7.0 Update 3i / 8.0 / 8.0 Update 1 Citrix Hypervisor 8.2 LTSR CU1
<b>Chipset</b>	Intel® C741 Chipset	<b>Power Supply</b>	Supports up to 1600W
<b>Memory</b>	8-Channel DDR5 memory, 8 x DIMM slots RDIMM modules up to 96GB supported 3DS RDIMM modules up to 256GB supported Memory speed: Up to 4800 MHz	<b>No. of Bus Bars</b>	1 x 48V Bus Bar
<b>LAN</b>	1 x 10/100/1000 management LAN		
<b>Storage</b>	10 x 9.5mm E1.S NVMe hot-swappable bays		
<b>Expansion Slots</b>	2 x FHHL PCIe Gen5 x16 slots 1 x LP PCIe Gen5 x8 slot 1 x M.2 slot: SATA, supports 2242/2260/2280/22110		



Learn more about GIGABYTE server, visit <https://www.gigacomputing.com>

\* All specifications are subject to change without notice. Please visit our website for the latest information.

\* Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.

\* All other brands, logos and names are property of their respective owners.

© 2023 Giga Computing Technology Co., Ltd. All rights reserved.

Engineered by

