How to Load the AORUS Sensor Panel Skin?

To use the AORUS sensor panel and display it on your secondary screen, follow the steps below to complete the required settings.

1 Set up the secondary display

Once you have connected the secondary screen, make sure to arrange your displays correctly. Right-click on the taskbar at the bottom of the screen and select **Taskbar Settings**. Under **Taskbar behaviors**, uncheck **Show my taskbar on all displays**.

(- Settings		- 0
gbt Local Account	Personalization > Taskbar	
find a utilize	Pes menu Show pen menu loon when pen is in use	on 🕘
-	Touch keyboard ison	When no keyboard attached $~\sim~$
System System Silvetooth & devices	Vetual touchpad Aways show virtual touchpad icon	or 💌
Network & internet Personalization	Other system tray icons Show or hide additional system tray icons	v
Apps	Taskbar behaviors Taskbar alignment, badging, automatically hide, and multiple displays	^
 Accounts Time & language 	Taşibar alişivment	Center ~
60 Gaming	Automatically hide the taskbar	
X Accessibility	Show badges on taskbar apps	
Privacy & security Windows Update		
	Show my taskbar on all displays by	
	When using multiple displays show my taskhar apos	All taskbara 🤟
	Share any window from my taskbar	
	Select the far corner of the taskbar to show the desktop	
	Show seconds in system tray clock (uses more power)	
	Get help	

Then, right-click on the desktop and select **Display settings**. Drag and drop each display to rearrange them according to their physical layout on your desktop. Make sure **Extend these displays** is selected.



Tip: You can use a third-party app to lock the mouse to your primary screen .

2 Download, install, and tune HWiNFO and Rainmeter

Before installing the AORUS Sensor Panel, install the two applications first. Visit the official websites of the three applications and download the latest version.

• <u>HWiNFO</u> (https://www.hwinfo.com/)

🔠 Setup - HWiNFO64	– D X
	Welcome to the HWiNFO64 Setup Wizard
	This will install HWINEO64 v7.68 on your computer.
	It is recommended that you dose all other applications before continuing.
	Click Next to continue, or Cancel to exit Setup.
	Next > N Cancel

Configure HWiNFO64

Open the System tray on the taskbar corner, right-click on the "HWiNFO64" icon and then select **Settings**. Configure HWiNFO64 with the recommended options as shown. Note: You need to re-enable the **Shared Memory Support** option in HWiNFO64 every 12 hours or you can install HWiNFO64 Pro.

ieneral / User Interface Safety SMBus / I2C	Driver Management License Manager	nent
Show System Summary on Startup	Wake disabled GPU	s
Show Sensors on Startup	Wake disabled GPU	s (Extended)
Minimize Main Window on Startup	Poll Sleeping GPUs	
Minimize Sensors on Startup	🕗 Reorder GPUs	
Minimize Sensors instead of closing	Prefer AMD ADL	
Show Welcome Screen and Progress		
Validate Window Positions	Remember Preference	245
Auto Start		Color Mode
Automatic Update	Backup User	O Default (Grey)
Flush Buffers on Start	Settings	O Default (Black)
Snapshot CPU Polling		O Disabled (Light)
Shared Memory Support	Reset Preferences	
V12-HOOR LIMIT		Theme:
Language:	Charle for the datas	GIGABYTE AORUS
English	Check for Opdates	

• Rainmeter



Configure Rainmeter

Open the System tray on the taskbar corner, right-click the "Rainmeter" icon to display the **Manage Rainmeter** window. Before you load the AORUS Sensor Panel skin, you can clear the default skins in the top-right corner. Unload the default skins by right-clicking on each of the windows and selecting **Unload skin**.

			- 19 B		02:46	
Skins Layouts Game	mode Settings			Wednesday	06.	.09.20
Active skins 🔹 🖡		Load Refresh	Edit		SYSTEM	
- illustro				CPU Usage		
	Authon			SWAP Usage		2
	License					
	Information:				DISKS	
				<u>C:\</u>	31.5 GB/118.4	GB u
				Div	illustro\Disk	
					Variants	
					illustro	
	Coordinators	0 miles and 1			Settings	
	coordinates.	Oisplay monit			Manage skin	
	Position:	Draggable			Edit skin	
	Load order:	Keep on screen			Refresh skin	
	Transparency:	Save position		- 10 C	Rainmeter	
	On hover:	Snap to edges			Unload skin	1
create moskin package						

3 Download and install the AORUS Sensor Panel Skin

Visit the GIGABYTE website and download the AORUS Sensor Panel skin (https://www.gigabyte. com/FileUpload/Global/KeyFeature/2496/innergigabyte/download/AORUS-Sensor-Panel.rmskin.zip). Install the AORU Sensor Panel and you will see the installed AORUS skin listed on the left-hand side panel of the Manage Rainmeter window.

		1	Skins	Layouts Game mode Settings	
Name: AORUS Senso Authon: AORUS Version: 1.1 ncluded components: Name Skins @ AORUS Plugins	Action Add			Author Verino License Information:	Load
HWiNFO.dll	Add			Coordinates:	
				Position:	
				Load order:	Kee

4 Load the AORUS Sensor Panel Skin on Rainmeter

To correctly display the AORU Sensor Panel, be sure to do the following steps. Step 1:

Open HWiNFO64. Go to Documents\Rainmeter\Skins\AORUS\@Resources, launch HWiNFOSharedMemoryViewer.exe and open the Notepad file named Titles, Meters and Icons.

🚞 @Resources	× +			-	o ×
$\leftarrow \rightarrow \uparrow$	C G Start backup > ···· S	Skins > AORUS > @Re	esources >	Search @Res	ources
🕀 New - 🏑	0 6 0 6 0	↑↓ Sort ~ 🛛 🔳 View ~			📑 Details
 ↔ Home ➡ Gallery → OneDrive → Desktop # → Downloads # ➡ Documents # 	Name Fents GFs GFs Finds Find	Date modified 1/31/2024 3:30 PM 1/31/2024 3:30 PM 1/31/2024 3:30 PM 1/31/2024 3:30 PM 1/31/2024 3:30 PM 1/31/2024 3:30 PM 1/31/2024 3:30 PM	Type File folder File folder File folder File folder Application exten INC File INC File	Size 97 KB 1 KB 3 KB	
Pictures *	HWiNFOSharedMemoryViewer.exe	1/31/2024 3:30 PM 1/31/2024 3:30 PM	Application INC File	875 KB 3 KB	
> 🜉 This PC	Tritles, Meters and Icons.inc	1/31/2024 3:42 PM	INC File	15 KB	

Step 2:

On the **HWiNFO Shared Memory Viewer** window, look for and select the GPU sensor. Under the **Sensor Details** section, copy the ID in the **Instance** column and paste it to replace the original value in "GPUHWiNFOSensorInstance" on the Notepad window. Save the changes to Notepad and close.

Local Machine		×	Remote Host ID	12 20 20 20 20 20 20 20 20 20 20 20 20 20
- System:	IGABYTE Z790 AORUS P	ROX		File Edit View
 ■ CPU [#0] ■ Memory 1 ■ CPU [#0] 	: Intel Care (9-14900K : Intel Care (9-14900K: D : Intel Care (9-14900K: E : Intel Care (9-14900K: C imings : Intel Care (9-14900K: P	ITS inhanced :-State Residency verformance Limit Rea:	ons	;Titles, Meters and Icons
GIGABYT	2790 AORUS PRO X (IT 2790 AORUS PRO X (IT IM [#3] (BANK 0/DDR5-8	E IT8689E) E IT87952E) 12)		[Variables]
E-S.M.A.R.	XTOR PX-128S3C (P027 NVIDIA GeForce GTX 16	(P02720126424) 20126424 550-		GPUHW1NF0SensorInstance=0x14
Sensor Det	ails	Barres 17 8126		;Motherboand
Original Nam			ID	oopy to here
GPU [#1]: 1	VIDIA GeForce GTX 165	0:	0xe0002000	Mame
Current Nam			Instance	[CustomMBnametext]
GPU [#1]: 1	VIDIA Genorce GTX 165	0:	0.014	: (ustom MB name to avoid the brand name for
Entry Deta	ls			Scuscom no name to avoid the brand name for
Original Nam	1		Values	meter=string
Current Nam				FONTFACE=AUKUS
Concinentation	-		Minimum	StringAlign=Left
ID	Type	Units	Maximum	Text=Z790 AORUS PRO
			Average	FontColor=494949
				FontSize=21
			Reload Close	Antialias=1
				X=220
				V-20

Step 3:

On the **Manage Rainmeter** window, double-click the AORUS skin folder to expand and select the ".ini" file. Click the **Load** button on the right to load AORUS Sensor Panel skin.

Skins Layouts Game	mode Settings		
Active skins Active skins ACRUS ACRUS ACRUS Sensor PaneLini Tillustro	AORUS Sensor Panel AORUS Author: AORUS Version: 1.03 License: Information: AORUS	. ini Lou Rainmeter skin for sene	ad Ref sh Edit
	Coordinates:		Display monitor
	Coordinates: Position:		Display monitor +
	Coordinates: Position: Load order:		Display monitor • Click through Draggable Kaep on screen
	Coordinates: Position: Load order: Transparency:		Display monitor • Click through Dragable Keep on screen Save position

Step 4:

Once the AORUS Sensor Panel appears on the desktop, you can drag it to your secondary display.

	Z790 A	ORUS P	R0 💥		15:43 P	M 01/31/20)24
	Intel Core	i9-14900K		GeForce	2 GTX 1650		
	CPU Clock		A384	FPS	GPU Power	- A.D.A.	
	550	О мнг	80°C	41 max: 61	5 w max: 15 w	34°C	
	CPU Usage	Vcore	CPU Power	GPU Usage	GPU Clock	GPU Mem. Cl	ock
N.	2.2 %	0.704 v	6 W max: 70 w	9.0 %	- 300 M	202 1Hz	MHz
	SYSTEM INFO.			NETWO	RK 🗟		ł
	Mem. Usage	Memory Clock	System Uptime	▲ 0.0	B/s		
ADRUS	22.3 %	4800 MH	iz 02:41	▼ 0.0	B/s	0	0 X