

Qualified Vendors List (QVL) (Matisse)

Speed	Module Supplier	Density	# of Ranks x DRAM devices	Module P/N.	SS/DS	Chip Brand	Chip P/N.	Timing	Voltage	Memory socket support		XMP	Native
										1	2		
2133	V-Color	8GB	1Rx8	TE48G21S815	SS	SKHynix		CL15	1.2v	V	V		v
2133	V-Color	8GB	1Rx8	TC48G21S815-IMS	SS			CL15	1.2v	V	V		v
2133	V-Color	16GB	2Rx8	TE416G21D815	DS	SKHynix		CL15	1.2v	V	V		v

• When running XMP at **DDR4 3200 MHz or higher**, the system's stability depends on the CPU's capabilities.
當執行XMP至**DDR4 3200MHz或是更高**，系統的穩定性會依據CPU的效能而有所差異

• Memory modules listed as above is for reference only. Due to massive memory models in market, we can only verify some of them.
以下所列的記憶體模組僅供參考，因市面上的記憶體模組眾多，我們無法一一驗證

• When enabling Dual Channel mode with two or four memory modules, it is recommended that using the same capacity, brand, speed, and chips of memory modules and also installed in the same color of DDR4 slots.
若要安裝兩支或四支DDR4記憶體模組，建議您使用相同容量/ 廠牌/ 速度/ 顆粒等之記憶體模組。