

"G241-G40" Qualification Vender List

Please contact FAE support for below orange blocks

Intel CPU										
Product Name	Code Name	Q-Spec	Stepping	Cache	System Bus	# of Cores	Processor Base Frequency	Max Turbo Frequency	TDP	Memory Types
Purley - Intel® Xeon® Processor Scalable Family										
Intel® Xeon® Processor Platinum 8176	SKYLAKE-S	QM03	H0	38.5 MB L3	10.4 GT/s	28	2.10 GHz	3.80 GHz	165 W	DDR4-2666
Intel® Xeon® Processor Platinum 8176M	SKYLAKE-S	QM7R	H0	38.5 MB L3	10.4 GT/s	28	2.10 GHz	3.80 GHz	165 W	DDR4-2666
Intel® Xeon® Processor Platinum 8170	SKYLAKE-S	QM0C	H0	35.75 MB L3	10.4 GT/s	26	2.10 GHz	3.70 GHz	165 W	DDR4-2666
Intel® Xeon® Processor Platinum 8164	SKYLAKE-S	Q MS8	H0	35.75 MB L3	10.4 GT/s	26	2.00 GHz	3.70 GHz	150 W	DDR4-2666
Intel® Xeon® Processor Platinum 8160	SKYLAKE-S	QMRV	H0	33 MB L3	10.4 GT/s	24	2.10 GHz	3.70 GHz	150 W	DDR4-2666
Intel® Xeon® Processor Platinum 8160T	SKYLAKE-S	QMRG	H0	33 MB L3	10.4 GT/s	24	2.10 GHz	3.70 GHz	150 W	DDR4-2666
Intel® Xeon® Processor Platinum 8153	SKYLAKE-S	QMS7	H0	22 MB L3	10.4 GT/s	16	2.00 GHz	2.80 GHz	125 W	DDR4-2666
Intel® Xeon® Processor Gold 6152	SKYLAKE-S	QMRZ	H0	30.25 MB L3	10.4 GT/s	22	2.10 GHz	3.70 GHz	140 W	DDR4-2666
Intel® Xeon® Processor Gold 6150	SKYLAKE-S	QM06	H0	24.75 MB L3	10.4 GT/s	18	2.70 GHz	3.70 GHz	165 W	DDR4-2666
Intel® Xeon® Processor Gold 6148	SKYLAKE-S	QMS1	H0	27.5 MB L3	10.4 GT/s	20	2.40 GHz	3.70 GHz	150 W	DDR4-2666
Intel® Xeon® Processor Gold 6146	SKYLAKE-S	QN7C	H0	24.75 MB L3	10.4 GT/s	12	3.20 GHz	4.20 GHz	165 W	DDR4-2666
Intel® Xeon® Processor Gold 6144	SKYLAKE-S	QN7D	H0	24.75 MB L3	10.4 GT/s	8	3.50 GHz	4.20 GHz	150 W	DDR4-2666
Intel® Xeon® Processor Gold 6142	SKYLAKE-S	QMRT	H0	22 MB L3	10.4 GT/s	16	2.60 GHz	3.70 GHz	150 W	DDR4-2666
Intel® Xeon® Processor Gold 6142M	SKYLAKE-S	QMRW	H0	22 MB L3	10.4 GT/s	16	2.60 GHz	3.70 GHz	150 W	DDR4-2666
Intel® Xeon® Processor Gold 6140M	SKYLAKE-S	QMRU	H0	24.75 MB L3	10.4 GT/s	18	2.30 GHz	3.70 GHz	140 W	DDR4-2666
Intel® Xeon® Processor Gold 6140	SKYLAKE-S	QMRS	H0	24.75 MB L3	10.4 GT/s	18	2.30 GHz	3.70 GHz	140 W	DDR4-2666
Intel® Xeon® Processor Gold 6138T	SKYLAKE-S	Q MS9	H0	27.5 MB L3	10.4 GT/s	20	2.00 GHz	3.70 GHz	125 W	DDR4-2666
Intel® Xeon® Processor Gold 6138	SKYLAKE-S	QMS0	H0	27.5 MB L3	10.4 GT/s	20	2.00 GHz	3.70 GHz	125 W	DDR4-2666
Intel® Xeon® Processor Gold 6136	SKYLAKE-S	QMRX	H0	24.75 MB L3	10.4 GT/s	12	3.00 GHz	3.70 GHz	150 W	DDR4-2666
Intel® Xeon® Processor Gold 6134	SKYLAKE-S	QMRL	H0	24.75 MB L3	10.4 GT/s	8	3.20 GHz	3.70 GHz	130 W	DDR4-2666
Intel® Xeon® Processor Gold 6132	SKYLAKE-S	QN33	H0	19.25 MB L3	10.4 GT/s	14	2.60 GHz	3.70 GHz	140 W	DDR4-2666
Intel® Xeon® Processor Gold 6130T	SKYLAKE-S	QN38	H0	22 MB L3	10.4 GT/s	16	2.10 GHz	3.70 GHz	125 W	DDR4-2666
Intel® Xeon® Processor Gold 6130	SKYLAKE-S	QMS6	H0	22 MB L3	10.4 GT/s	16	2.10 GHz	3.70 GHz	125 W	DDR4-2666
Intel® Xeon® Processor Gold 6128	SKYLAKE-S	QN34	H0	19.25 MB L3	10.4 GT/s	6	3.40 GHz	3.70 GHz	115 W	DDR4-2666
Intel® Xeon® Processor Gold 6126T	SKYLAKE-S	QN39	H0	19.25 MB L3	10.4 GT/s	12	2.60 GHz	3.70 GHz	125 W	DDR4-2666
Intel® Xeon® Processor Gold 6126	SKYLAKE-S	QMRV	H0	19.25 MB L3	10.4 GT/s	12	2.60 GHz	3.70 GHz	125 W	DDR4-2666
Intel® Xeon® Processor Gold 5122	SKYLAKE-S	QMRN	H0	16.5 MB L3	10.4 GT/s	4	3.60 GHz	3.70 GHz	105 W	DDR4-2666
Intel® Xeon® Processor Gold 5120T	SKYLAKE-S	QMXL	M0	19.25 MB L3	10.4 GT/s	14	2.20 GHz	3.20 GHz	105 W	DDR4-2400
Intel® Xeon® Processor Gold 5120	SKYLAKE-S	QMXJ	M0	19.25 MB L3	10.4 GT/s	14	2.20 GHz	3.20 GHz	105 W	DDR4-2400
Intel® Xeon® Processor Gold 5119T	SKYLAKE-S	QN11	M0	19.25 MB L3	10.4 GT/s	14	1.90 GHz	3.20 GHz	85 W	DDR4-2400
Intel® Xeon® Processor Gold 5118	SKYLAKE-S	QMXH	M0	16.5 MB L3	10.4 GT/s	12	2.30 GHz	3.20 GHz	105 W	DDR4-2400
Intel® Xeon® Processor Gold 5115	SKYLAKE-S	QMXG	M0	13.75 MB L3	10.4 GT/s	10	2.40 GHz	3.20 GHz	85 W	DDR4-2400
Intel® Xeon® Processor Silver 4116T	SKYLAKE-S	QN7B	M0	16.5 MB L3	9.6 GT/s	12	2.10 GHz	3.00 GHz	85 W	DDR4-2400
Intel® Xeon® Processor Silver 4116	SKYLAKE-S	QN1J	M0	16.5 MB L3	9.6 GT/s	12	2.10 GHz	3.00 GHz	85 W	DDR4-2400
Intel® Xeon® Processor Silver 4114T	SKYLAKE-S	QN7A	U0	13.75 MB L3	9.6 GT/s	10	2.20 GHz	3.00 GHz	85 W	DDR4-2400
Intel® Xeon® Processor Silver 4114	SKYLAKE-S	QN0B	U0	13.75 MB L3	9.6 GT/s	10	2.20 GHz	3.00 GHz	85 W	DDR4-2400
Intel® Xeon® Processor Silver 4112	SKYLAKE-S	QN0E	U0	8.25 MB L3	9.6 GT/s	4	2.60 GHz	3.00 GHz	85 W	DDR4-2400
Intel® Xeon® Processor Silver 4110	SKYLAKE-S	QN09	U0	11 MB L3	9.6 GT/s	8	2.10 GHz	3.00 GHz	85 W	DDR4-2400
Intel® Xeon® Processor Silver 4109T	SKYLAKE-S	QN0F	U0	11 MB L3	9.6 GT/s	8	2.00 GHz	3.00 GHz	70 W	DDR4-2400
Intel® Xeon® Processor Silver 4108	SKYLAKE-S	QN0A	U0	11 MB L3	9.6 GT/s	8	1.80 GHz	3.00 GHz	85 W	DDR4-2400
Intel® Xeon® Processor Bronze 3106	SKYLAKE-S	QN0C	U0	11 MB L3	9.6 GT/s	8	1.70 GHz	None	85 W	DDR4-2133
Intel® Xeon® Processor Bronze 3104	SKYLAKE-S	QN0D	U0	8.25 MB L3	9.6 GT/s	6	1.70 GHz	None	85 W	DDR4-2133
CascadeLake - Intel® Xeon® Processor Scalable Family										
Intel® Xeon® Processor Platinum 8276M	CascadeLake SP	QRAW	B0	38.5MB	10.4 GT/s	28	2.2 GHz	4.00 GHz	165W	DDR4-2933
Intel® Xeon® Processor Platinum 8276L	CascadeLake SP	QRAV	B0	38.5MB	10.4 GT/s	28	2.20 GHz	4.00 GHz	165W	DDR4-2933

Intel® Xeon® Processor Platinum 8276	CascadeLake SP	QPJT	A0	38.5MB	10.4 GT/s	28	2.20 GHz	4.00 GHz	165W	DDR4-2933
Intel® Xeon® Processor Platinum 8260M	CascadeLake SP	QRC4	B0	33MB	10.4 GT/s	24	2.40 GHz	3.90 GHz	165W	DDR4-2933
Intel® Xeon® Processor Platinum 8260Y	CascadeLake SP	QRC1	B0	35.75MB	10.4 GT/s	24	2.40 GHz	3.90 GHz	165W	DDR4-2933
Intel® Xeon® Processor Platinum 8260	CascadeLake SP	QRC3	B0	33MB	10.4 GT/s	24	2.40 GHz	3.90 GHz	165W	DDR4-2933
Intel® Xeon® Processor Platinum 8260L	CascadeLake SP	QRC2	B0	33MB	10.4 GT/s	24	2.40 GHz	3.90 GHz	165W	DDR4-2933
Intel® Xeon® Processor Platinum 8256	CascadeLake SP	QRAP	B0	16.5MB	10.4 GT/s	4	3.80 GHz	3.90 GHz	105W	DDR4-2933
Intel® Xeon® Processor Platinum 8253	CascadeLake SP	QRAN	B0	22MB	10.4 GT/s	16	2.20 GHz	3.00 GHz	125W	DDR4-2933
Intel® Xeon® Processor Gold 6262V	CascadeLake SP	QS2B	B1	33MB	10.4 GT/s	24	1.90 GHz	3.60 GHz	135W	DDR4-2400
Intel® Xeon® Processor Gold 6252	CascadeLake SP	QRAL	B0	33MB	10.4 GT/s	24	2.10 GHz	3.70 GHz	150W	DDR4-2933
Intel® Xeon® Processor Gold 6248	CascadeLake SP	QRAK	B0	27.5MB	10.4 GT/s	20	2.50 GHz	3.90 GHz	150W	DDR4-2933
Intel® Xeon® Processor Gold 6246	CascadeLake SP	QS1Q	B1	24.75MB	10.4 GT/s	8	3.30 GHz	4.20 GHz	165W	DDR4-2933
Intel® Xeon® Processor Gold 6244	CascadeLake SP	QRAJ	B0	24.75MB	10.4 GT/s	8	3.60 GHz	4.40 GHz	150W	DDR4-2933
Intel® Xeon® Processor Gold 6242	CascadeLake SP	QRAH	B0	22MB	10.4 GT/s	16	2.80 GHz	3.90 GHz	150W	DDR4-2933
Intel® Xeon® Processor Gold 6240Y	CascadeLake SP	QRBX	B0	24.75MB	10.4 GT/s	18	2.60 GHz	3.90 GHz	150W	DDR4-2933
Intel® Xeon® Processor Gold 6240M	CascadeLake SP	QS25	B1	24.75MB	10.4 GT/s	18	2.60 GHz	3.90 GHz	150W	DDR4-2933
Intel® Xeon® Processor Gold 6240L	CascadeLake SP	QS26	B1	24.75MB	10.4 GT/s	18	2.60 GHz	3.90 GHz	150W	DDR4-2933
Intel® Xeon® Processor Gold 6240	CascadeLake SP	QRAG	B0	24.75MB	10.4 GT/s	18	2.60 GHz	3.90 GHz	150W	DDR4-2933
Intel® Xeon® Processor Gold 6238M	CascadeLake SP	QS27	B1	30.25MB	10.4 GT/s	22	2.10 GHz	3.70 GHz	140W	DDR4-2933
Intel® Xeon® Processor Gold 6238T	CascadeLake SP	QRBW	B0	30.25MB	10.4 GT/s	22	1.90 GHz	3.70 GHz	125W	DDR4-2933
Intel® Xeon® Processor Gold 6238L	CascadeLake SP	QS28	B1	30.25MB	10.4 GT/s	22	2.10 GHz	3.70 GHz	140W	DDR4-2933
Intel® Xeon® Processor Gold 6238	CascadeLake SP	QS1S	B1	30.25MB	10.4 GT/s	22	2.10 GHz	3.70 GHz	140W	DDR4-2933
Intel® Xeon® Processor Gold 6234	CascadeLake SP	QS1U	B1	24.75MB	10.4 GT/s	8	3.30 GHz	4.00 GHz	130W	DDR4-2933
Intel® Xeon® Processor Gold 6230T	CascadeLake SP	QS1Y	B1	27.5MB	10.4 GT/s	20	2.10 GHz	3.90 GHz	125W	DDR4-2933
Intel® Xeon® Processor Gold 6230N	CascadeLake SP	QS1X	B1	27.5MB	10.4 GT/s	20	2.30 GHz	3.50 GHz	125W	DDR4-2933
Intel® Xeon® Processor Gold 6230	CascadeLake SP	QRAD	B0	27.5MB	10.4 GT/s	20	2.10 GHz	3.90 GHz	125W	DDR4-2933
Intel® Xeon® Processor Gold 6226	CascadeLake SP	QS1V	B1	19.25MB	10.4 GT/s	12	2.70 GHz	3.70 GHz	125W	DDR4-2933
Intel® Xeon® Processor Gold 6222V	CascadeLake SP	QS2C	B1	27.5MB	10.4 GT/s	20	1.80 GHz	3.60 GHz	115W	DDR4-2400
Intel® Xeon® Processor Gold 5220T	CascadeLake SP	QS1R	B1	24.75MB	10.4 GT/s	18	1.90 GHz	3.90 GHz	105W	DDR4-2666
Intel® Xeon® Processor Gold 5220S	CascadeLake SP	QS1Z	B1	24.75MB	10.4 GT/s	18	2.70 GHz	3.90 GHz	125W	DDR4-2666
Intel® Xeon® Processor Gold 5220	CascadeLake SP	QRGH	L0	24.75MB	10.4 GT/s	18	2.20 GHz	3.90 GHz	125W	DDR4-2666
Intel® Xeon® Processor Gold 5218B	CascadeLake SP	QRGE	L0	22MB	10.4 GT/s	16	2.30 GHz	3.90 GHz	125W	DDR4-2666
Intel® Xeon® Processor Gold 5218N	CascadeLake SP	QRGD	L0	22MB	10.4 GT/s	16	2.30 GHz	3.70 GHz	105W	DDR4-2666
Intel® Xeon® Processor Gold 5218T	CascadeLake SP	QS1T	B1	22MB	10.4 GT/s	16	2.10 GHz	3.80 GHz	105W	DDR4-2666
Intel® Xeon® Processor Gold 5218	CascadeLake SP	QRA9	L0	22MB	10.4 GT/s	16	2.30 GHz	3.90 GHz	125W	DDR4-2666
Intel® Xeon® Processor Gold 5217	CascadeLake SP	QRGC	L0	11MB	10.4 GT/s	8	3.00 GHz	3.70 GHz	115W	DDR4-2666
Intel® Xeon® Processor Gold 5215L	CascadeLake SP	QRGB	L0	13.75MB	10.4 GT/s	10	2.50 GHz	3.40 GHz	85W	DDR4-2666
Intel® Xeon® Processor Gold 5215M	CascadeLake SP	QRGA	L0	13.75MB	10.4 GT/s	10	2.50 GHz	3.40 GHz	85W	DDR4-2666
Intel® Xeon® Processor Gold 5215	CascadeLake SP	QRG9	L0	13.75MB	10.4 GT/s	10	2.50 GHz	3.40 GHz	85W	DDR4-2666
Intel® Xeon® Processor Silver 4216	CascadeLake SP	QRG8	L0	22MB	9.6 GT/s	16	2.10 GHz	3.20 GHz	100W	DDR4-2133
Intel® Xeon® Processor Silver 4215	CascadeLake SP	QRG7	L0	11MB	9.6 GT/s	8	2.50 GHz	3.50 GHz	85W	DDR4-2133
Intel® Xeon® Processor Silver 4214Y	CascadeLake SP	QRHY	L0	16.5MB	9.6 GT/s	12	2.20 GHz	3.20 GHz	85W	DDR4-2133
Intel® Xeon® Processor Silver 4214	CascadeLake SP	QRG6	L0	16.5MB	9.6 GT/s	12	2.20 GHz	3.20 GHz	85W	DDR4-2133
Intel® Xeon® Processor Silver 4210	CascadeLake SP	QPJF	R0	13.75MB	9.6 GT/s	10	2.20 GHz	3.20 GHz	85W	DDR4-2133
Intel® Xeon® Processor Silver 4209T	CascadeLake SP	QPJM	R0	11MB	9.6 GT/s	8	2.20 GHz	3.20 GHz	70W	DDR4-2133
Intel® Xeon® Processor Silver 4208	CascadeLake SP	QPJG	R0	11MB	9.6 GT/s	8	2.10 GHz	3.20 GHz	85W	DDR4-2133
Intel® Xeon® Processor Bronze 3204	CascadeLake SP	QPJK	R0	8.25MB	9.6 GT/s	6	1.90 GHz	1.90 GHz	85W	DDR4-2133
CascadeLake refresh - Intel® Xeon® Processor Scalable Family										
Intel® Xeon® Processor Gold 6240R	CascadeLake refresh	SRGZ8	B1	35.75MB	10.4 GT/s	24	2.4 GHz	4.0 GHz	165W	DDR4-2933
Intel® Xeon® Processor Gold 6238R	CascadeLake refresh	SRGZ9	B1	38.50MB	10.4 GT/s	28	2.2 GHz	4.0 GHz	165W	DDR4-2933

Intel® Xeon® Processor Gold 6230R	CascadeLake refresh	SRGZA	B1	35.75MB	10.4 GT/s	26	2.1GHz	4.0 GHz	150W	DDR4-2933
Intel® Xeon® Processor Gold 6226R	CascadeLake refresh	SRGZC	B1	22MB	10.4 GT/s	16	2.9 GHz	3.9 GHz	150W	DDR4-2933
Intel® Xeon® Processor Silver 4215R	CascadeLake refresh	SRGZE	B1	11MB	10.4 GT/s	8	3.2 GHz	4.0 GHz	130W	DDR4-2400
Intel® Xeon® Processor Gold 5220R	CascadeLake refresh	SRGZP	B1	35.75MB	10.4 GT/s	24	2.2 GHz	4.0 GHz	150W	DDR4-2666
Intel® Xeon® Processor Gold 5218R	CascadeLake refresh	SRGZ7	B1	27.50MB	10.4GT/s	20	2.1GHz	4.0 GHz	125W	DDR4-2666
Intel® Xeon® Processor Silver 4214R	CascadeLake refresh	QSKT	L1	16.5MB	9.6 GT/s	12	2.4 GHz	3.5 GHz	100W	DDR4-2400
Intel® Xeon® Processor Silver 4210R	CascadeLake refresh	QSL1	R1	13.75MB	9.6 GT/s	10	2.4 GHz	3.2 GHz	100W	DDR4-2400
Intel® Xeon® Processor Bronze 3206R	CascadeLake refresh	QSL2	R1	11MB	9.6 GT/s	8	1.9 GHz	1.9 GHz	85W	DDR4-2133

Montage Jintide® Processor Scalable Family

Montage Jintide® C24601	Jintide	SREUN	H0	33MB	10.4 GT/s	24	2.1 GHz	3.7 GHz	150W	DDR4
Montage Jintide® C10201	Jintide	SREUK	H0	13.75MB	9.6 GT/s	10	2.2 GHz	3.0 GHz	85W	DDR4
Montage Jintide® C08101	Jintide	SREUL	H0	11MB	9.6 GT/s	8	2.1 GHz	3.0 GHz	85W	DDR4
Montage Jintide® C16401	Jintide	SREUM	H0	22MB	10.4 GT/s	16	2.1 GHz	3.7 GHz	125W	DDR4
Montage Jintide® C12301	Jintide	SREUH	H0	16.5MB	10.4 GT/s	12	2.3 GHz	3.2 GHz	105W	DDR4
Montage Jintide® C14501	Jintide	SREUJ	H0	19.25MB	10.4 GT/s	14	2.2 GHz	3.2 GHz	105W	DDR4

Memory (Memory actually maximum frequency will follow memory controller's spec of CPU you used)

Product Name	Memory Type	Module Supplier	Size	Chip Brand	Rank	Voltage	Data Transfer Rate	Error Correction	CAS Latency	Pins
--------------	-------------	-----------------	------	------------	------	---------	--------------------	------------------	-------------	------

RDIMM

M393A8K40B22-CWD6Q	DDR4	Samsung	64GB	Samsung	2S2Rx4	1.2v	2666MHz	ECC Registered	19	288-pin
CT32G4RFD4266-2G6H1.001	DDR4	CRUCIAL	32GB	Micron	2Rx4	1.2v	2666MHz	ECC Registered	19	288-pin
MTA36ASF4G72PZ-2G6H1QG	DDR4	CRUCIAL	32GB	Micron	2Rx4	1.2v	2666MHz	ECC Registered	19	288-pin
HMA84GR7AFR4N-VKT3	DDR4	SKhynix	32GB	Skhynix-Montage	2Rx4	1.2v	2666MHz	ECC Registered	19	288-pin
KSM26RD4/32HAI	DDR4	Kingston	32GB	Skhynix-IDT	2Rx4	1.2v	2666MHz	ECC Registered	19	288-pin
TR432G26D419-VKA	DDR4	V-color	32GB	Skhynix-Inphi	2Rx4	1.2v	2666MHz	ECC Registered	19	288-pin
CT32G4RFD4293.2G9E2.001	DDR4	CRUCIAL	32GB	Micron	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
CT32G4RFD4293.36FE2	DDR4	CRUCIAL	32GB	Micron	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ-2G9E2TG	DDR4	Micron	32GB	Micron-Montage	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ-2G9E2VG	DDR4	Micron	32GB	Micron-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ-2G9E2UG	DDR4	Micron	32GB	Micron-Rambus	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
KSM29RD4/32MEI	DDR4	Kingston	32GB	Micron-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
CT8G4RFS8293.9FE1	DDR4	CRUCIAL	8GB	Micron	1Rx8	1.2v	2933MHz	ECC Registered	21	288-pin

CT8G4RFS8293-2G9E1.001	DDR4	CRUCIAL	8GB	Micron	1Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
MTA9ASF1G72PZ.2G9E1VG	DDR4	Micron	8GB	Micron-IDT	1Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
MTA9ASF1G72PZ.2G9E1UG	DDR4	Micron	8GB	Micron-Rambus	1Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
MTA9ASF1G72PZ.2G9E1TI	DDR4	Micron	8GB	Micron-Montage	1Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
CT16G4RFD8293.18FE1	DDR4	CRUCIAL	16GB	Micron	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
CT16G4RFD8293.2G9E1.001	DDR4	CRUCIAL	16GB	Micron	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
MTA18ASF2G72PDZ-2G9E1UG	DDR4	Micron	16GB	Micron-Rambus	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
MTA18ASF2G72PDZ-2G9E1VG	DDR4	Micron	16GB	Micron-IDT	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
KSM29RD8/16MEI	DDR4	Kingston	16GB	Micron-IDT	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
NT16GA72D8PBX3P-IX	DDR4	Nanya	16GB	Nanya-IDT	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
NT32GA72D4NBX3P-IX	DDR4	Nanya	32GB	Nanya-Montage or IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
M393A2K40DB2-CVFBQ	DDR4	Samsung	16GB	Samsung-IDT	1Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
M393A4K40DB2-CVFBQ	DDR4	Samsung	32GB	Samsung-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA18ASF2G72PDZ-2G9J3VI	DDR4	Micron	16GB	Micron-IDT	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
MTA18ASF2G72PDZ-2G9J3TI	DDR4	Micron	16GB	Micron-Montage	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
HMA81GR7CJR8N-WM TG	DDR4	SKhynix	8GB	SKhynix-IDT	1Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
KSM29RD4/32HDR	DDR4	Kingston	32GB	SKhynix-Rambus	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
M393A2K43DB2-CVFBQ	DDR4	Samsung	16GB	Samsung-IDT	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ-2G9J3TI	DDR4	Micron	32GB	Micron-Montage	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
KSM29RD8/16HDR	DDR4	Kingston	16GB	SKhynix-Rambus	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
RDIMM (Only support CascadeLake)										
M393A8G40MB2-CTD7Q	DDR4	Samsung	64GB	Samsung-IDT	2Rx4	1.2v	2666MHz	ECC Registered	19	288-pin
M393A8G40MB2-CVFBY	DDR4	Samsung	64GB	Samsung-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
CT64G4RFD4293-2G9B2.001	DDR4	Crucial	64GB	Micron-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF8G72PZ-2G9B2VI	DDR4	Crucial	64GB	Micron-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
HMAA8GR7MJR4N-WM T4	DDR4	SKhynix	64GB	SKhynix-Montage	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin

MTA36ASF8G72PZ-2G9E1TI	DDR4	Micron	64GB	Micron-Montage	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
M393A8G40AB2-CVFBY	DDR4	Samsung	64GB	Samsung-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA9ASF2G72PZ-2G9E1UI	DDR4	Micron	16GB	Micron-Rambus	1Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
MTA18ASF4G72PDZ-2G9E1TI	DDR4	Micron	32GB	Micron-Montage	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
LRDIMM										
HMAA8GL7AMR4N-VKTF	DDR4	SKhynix	64GB	SKhynix	4DRx4	1.2v	2666MHz	ECC Registered	17	288-pin
M386A8K40BM2-CTD7Q	DDR4	Samsung	64GB	Samsung	4DRx4	1.2v	2666MHz	ECC Registered	17	288-pin
M386A8K40CM2-CVFBY	DDR4	Samsung	64GB	Samsung-IDT	4DRx4	1.2v	2933MHz	ECC Registered	21	288-pin
Toshiba HDD (SAS HDD may need RAID Card support)										
Product Name	Type	Vendor	Form Factor	Format	Capacity	Interface Speed	Series	Cache	RPM	Encryption
Enterprise Hard Drives										
MG06ACA10TE	SATA	Toshiba	3.5"	512e	10TB	6Gb/s	Capacity	256MB	7200	N/A
MG07ACA14TE	SATA	Toshiba	3.5"	512e	14TB	6Gb/s	MG07ACA	256MB	7200	N/A
Seagate HDD (SAS HDD may need RAID Card support)										
Product Name	Type	Vendor	Form Factor	Format	Capacity	Interface Speed	Series	Cache	RPM	Encryption
Seagate Enterprise Capacity 2.5 HDD										
ST1000NX0303	SATA	Seagate	2.5"	4Kn	1TB	6Gb/s	EXOS 7E2000	128MB	7200	N/A
ST2000NX0243	SATA	Seagate	2.5"	4Kn	2TB	6Gb/s	Exos 7E2000 (Enterprise Capacity V.3)	128MB	7200	N/A
Seagate Enterprise Capacity 3.5 HDD										
ST14000NM0018	SATA	Seagate	3.5"	512e	14TB	6Gb/s	EXOS X14 (Enterprise Capacity)	256MB	7200	N/A
ST16000NM001G	SATA	Seagate	3.5"	512e/4Kn	16TB	6Gb/s	EXOS X16	256MB	7200	N/A
ST2000NM0008	SATA	Seagate	3.5"	512n	2TB	6Gb/s	EXOS 7E2	128MB	7200	N/A
ST10000NM017B	SATA	Seagate	3.5"	512e	10TB	6Gb/s	EXOS 7E10	256MB	7200	N/A
WD HDD(SAS HDD may need RAID Card support)										
Product Name	Type	Vendor	Form Factor	Format	Capacity	Interface Speed	Series	Cache	RPM	Encryption
Enterprise Hard Drives										
WUS721010ALE6L4	SATA	WD	3.5"	512e	10TB	6Gb/s	Ultrastar® DC HC330	256MB	7200	N/A
SATA/SAS SSD										
Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	FW			Note
SATA/SAS SSD										
MTFDDAK1T9TDN-1AT1ZABYY (5200 MAX)	SSD	Micron	2.5"	SATA	1.92TB	6Gb/s				
MZ-7LH1T9NE 883 DCT Series	SSD	Samsung	2.5"	SATA	1.92TB	6Gb/s				
SSDSC2KG019T8 D3-S4610 Series	SSD	Intel	2.5"	SATA	1.92TB	6Gb/s				
SSDSC2KB019T8 D3-S4510 Series	SSD	Intel	2.5"	SATA	1.92TB	6Gb/s				
XA960LE10063	SSD	Seagate	2.5"	SATA	960GB	6Gb/s				
XA480LE10063	SSD	Seagate	2.5"	SATA	480GB	6Gb/s				
SRE100-960G00210000	SSD	Phison	2.5"	SATA	960GB	6Gb/s				
SRE100-480G00210000	SSD	Phison	2.5"	SATA	480GB	6Gb/s				
SEDC500M/3840G DC500M Series	SSD	Kingston	2.5"	SATA	3.84TB	6Gb/s				
SEDC500M/1920G DC500M Series	SSD	Kingston	2.5"	SATA	1.92TB	6Gb/s				
SEDC500M/960G DC500M Series	SSD	Kingston	2.5"	SATA	960GB	6Gb/s				
SEDC500M/480G DC500M Series	SSD	Kingston	2.5"	SATA	480GB	6Gb/s				
ASR1100SS-240GT-B	SSD	Adata	2.5"	SATA	240GB	6Gb/s				

KHK61RSE960G	SSD	Toshiba	2.5"	SATA	960GB	6Gb/s				
MTFDDAK3T8TDS-1AW1ZABYY (5300 PRO)	SSD	Micron	2.5"	SATA	3.84TB	6Gb/s				
MTFDDAK1T9TDS-1AW1ZABYY (5300 PRO)	SSD	Micron	2.5"	SATA	1.92TB	6Gb/s				
SSB240GTLCG-D2-SME520GBT ESM1220 Series	SSD	Phison	2.5"	SATA	240GB	6Gb/s				
SSB480GTLCG-D2-SME520GBT ESM1220 Series	SSD	Phison	2.5"	SATA	480GB	6Gb/s				
SSB960GTLCG-D2-SME520GBT ESM1220 Series	SSD	Phison	2.5"	SATA	960GB	6Gb/s				
SSB1K9GTLOG-D2-SME520GBT ESM1220 Series	SSD	Phison	2.5"	SATA	1.92TB	6Gb/s				
PCIe SSD										
Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	Note			
PCIe SSD										
SSDPEDKX040T701 P4500 Series PCIe Gen3 x4 4TB	PCIe	Intel	PCI-E 3.0	PCIe(NVMe)	4TB	-				
Samsung PM1725a MZPLL1T6HEHP PCIe Gen3 x8 1.6TB	PCIe	Samsung	PCI-E 3.0	PCIe(NVMe)	1.6TB	-				
Netlist N1951 E3 NS1951AH33T2 Gen3 x8 3.2TB	PCIe	Netlist	PCI-E 3.0	PCIe(NVMe)	3.2TB	-				
Samsung PM1725b MZPLL3T2HAJQ PCIe Gen3 x8 3.2TB	PCIe	Samsung	PCI-E 3.0	PCIe(NVMe)	3.2TB	-				
M.2										
Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	Note			
M.2										
SSDPEKKA010T801 P4101 Series 1TB	M.2	Intel	2280	PCIe(NVMe)	1TB					
MZ-1LB960N 983 DCT Series	M.2	Samsung	22110	PCIe(NVMe)	960GB					
MZ-1LB1T9N 983 DCT Series	M.2	Samsung	22110	PCIe(NVMe)	1.92TB					
IM2P33F8-256GD	M.2	ADATA	2280	PCIe(NVMe)	256GB	-				
IM2P33F8-512GD	M.2	ADATA	2280	PCIe(NVMe)	512GB	-				
AF960GSTJA-YT1 ATP 960GB	M.2	ATP	2280	PCIe(NVMe)	960GB	-				
IM2P33F8-256GD1	M.2	ADATA	2280	PCIe(NVMe)	256GB	-				
IM2P33F8-512GD1	M.2	ADATA	2280	PCIe(NVMe)	512GB	-				
SATA DOM										
Product Name	Type	Vendor	Capacity	Flash Type	Max. Channels	Max. Power Consumption	Note			
SATA III										
Innodisk SATADOM-SL 3ME4 DESSL-64GM41BC1SCB	Vertical	INNODISK	64GB	MLC	1	0.734 W				
Innodisk SATADOM-SL 3ME4 DESSL-A28M41BCADCB-D33	Vertical	INNODISK	128GB	MLC	1	1.02 W				
Innodisk SATADOM-ML 3ME4 DESML-64GM41BCADCB	Vertical	INNODISK	64GB	MLC	2	0.815 W				
Innodisk SATADOM-SH 3ME4 DESSH-64GM41BC1SCB	Horizontal	INNODISK	64GB	MLC	2	1.27 W				
Innodisk SATADOM-SH TYPE C 3ME4 DESSC-64GM41BC1SCB	Horizontal	INNODISK	64GB	MLC	1	0.626 W				
RAID Cards										
Model	RAID-on-Chip Controller	Host Bus Type	Internal Ports	Internal Connectors	External Ports	External Connectors	Data Transfer Rates	Note		
GIGABYTE Storage Cards										
CSA3548	LSI SAS 3008	PCIe- x8 Gen3 x8 bus	-	-	8	2 x external Mini-SAS HD SFF8644	12Gb/s ports			
GPGPU Card (GPGPU server only)										
Product Name	Processor Cores	Memory Bandwidth (GB/sec)	VRAM	OpenGL	Microsoft DirectX	Graphics Card Power (W)	NVIDIA SLI / AMD CrossFire Ready	Note		
NVIDIA Tesla (http://www.NVIDIA.com/object/tesla-supercomputing-solutions.html)										
RTX6000 passive (TURING)	4608	624 GB/s	24GB			250 W				4 pcs
V100 (VOLTA) 32GB	5120	900 GB/s	32GB			250 W				4 pcs
V100S (VOLTA)	5120	1134 GB/s	32GB			250 W				4 pcs
T4 (TURING)	2560	320 GB/s	16GB			70 W				4 pcs
AMD Radeon Instinct										
MI50 (Vega20) 32GB	3840	1024GB/s	32GB			300 W				4 pcs
LAN Cards										

Product Name	Connector	System Interface Type	# of Ports	Data Rate	Note
GIGABYTE LAN Cards					
CLN4752	QSFP+	PCIe x8 Gen3 x8	Dual	40Gb/s per port	INTEL XL710
CLN4224	RJ-45	PCIe x8 Gen3 x4	Quad	10Gb/s per port	INTEL X550-AT2
CLN4M34	SFP28	PCIe Gen3 x16	Quad	10Gb/s per port	Mellanox ConnectX-4
Intel_10GbE					
Intel® Ethernet Converged Network Adapter X550-T2	RJ-45	PCIe v3.0 (8.0 GT/s)	Dual	10Gb/s per port	
Qlogic LAN Adapters					
QLE3442-RJ-CK	RJ-45	PCIe x8 Gen3 x8	Dual	10Gb/s per port	
Intel Omni-Path Host Fabric					
Intel® Omni-Path Host Fabric Adapters 100HFA016LS	QSFP28	PCIe v3.0 x16	Single	100Gb/s per port	
USB Device					
Product Name	Type	Vendor	Capacity	Note	
USB 3.0					
PURE CLASSIC X176B1FWBO75	HDD	Gigabyte	500G		
GoFlex STAA500305	HDD	Seagate	500G		
TOSHIBA CANVIO BASIC	HDD	Toshiba	500G		
S1-DS3-Plus	Device	CyberSLIM			