

"G262-IR0" Qualification Vender List

Please contact FAE support for below orange blocks

Intel CPU										
Product Name	Code Name	Q-Spec	Stepping	Cache	System Bus	# of Cores	Processor Base Frequency	Max Turbo Frequency	TDP	Memory Types
Intel® Xeon® Processor Platinum 8380	IceLake	QXC0	D1	60MB	11.2GT/s	40	2.30 GHz	3.40 GHz	270 W	DDR4-3200
Intel® Xeon® Processor Platinum 8368	IceLake	QWLL	D1	57MB	11.2GT/s	38	2.40 GHz	3.40 GHz	270 W	DDR4-3200
Intel® Xeon® Processor Platinum 8362	IceLake	QXTL	D2	48MB	11.2GT/s	32	2.80 GHz	3.60 GHz	265 W	DDR4-3200
Intel® Xeon® Processor Platinum 8360Y	IceLake	QXBZ	D1	54MB	11.2GT/s	36	2.40 GHz	3.50 GHz	250 W	DDR4-3200
Intel® Xeon® Processor Platinum 8352Y	IceLake	QWM3	D1	48MB	11.2GT/s	32	2.20 GHz	3.40 GHz	205 W	DDR4-3200
Intel® Xeon® Processor Platinum 8352M	IceLake	QXZ0	D2	48MB	11.2GT/s	32	2.30 GHz	3.50 GHz	185W	DDR4-3200
Intel® Xeon® Processor Gold 6346	IceLake	QWMD	D1	36MB	11.2GT/s	16	3.10 GHz	3.60 GHz	205 W	DDR4-3200
Intel® Xeon® Processor Gold 6342	IceLake	QXRU	M1	36MB	11.2GT/s	24	2.80 GHz	3.50 GHz	230 W	DDR4-3200
Intel® Xeon® Processor Gold 6338T	IceLake	QXS3	M1	36MB	11.2GT/s	24	2.10 GHz	3.40 GHz	165 W	DDR4-3200
Intel® Xeon® Processor Gold 6338N	IceLake	QWM6	D1	48MB	11.2GT/s	32	2.20 GHz	3.50 GHz	185 W	DDR4-2667
Intel® Xeon® Processor Gold 6338	IceLake	SRKJ9	D2	48MB	11.2GT/s	32	2.00 GHz	3.20 GHz	205 W	DDR4-3200
Intel® Xeon® Processor Gold 6336Y	IceLake	QXRV	M1	36MB	11.2GT/s	24	2.40 GHz	3.60 GHz	185 W	DDR4-3200
Intel® Xeon® Processor Gold 6330N	IceLake	QWLP	D1	42MB	11.2GT/s	28	2.20 GHz	3.40 GHz	165 W	DDR4-2667
Intel® Xeon® Processor Gold 6330	IceLake	QWMC	D1	42MB	11.2GT/s	28	2.00 GHz	3.10 GHz	205 W	DDR4-2933
Intel® Xeon® Processor Gold 6326	IceLake	QXS7	M1	24MB	11.2GT/s	16	2.90 GHz	3.50 GHz	185 W	DDR4-3200
Intel® Xeon® Processor Gold 5320T	IceLake	QXS6	M1	30MB	11.2GT/s	20	2.30 GHz	3.50 GHz	150 W	DDR4-2993
Intel® Xeon® Processor Gold 5320	IceLake	QXRT	M1	39MB	11.2GT/s	26	2.20 GHz	3.40 GHz	185 W	DDR4-2933
Intel® Xeon® Processor Gold 5318Y	IceLake	QXS2	M1	36MB	11.2GT/s	24	2.10 GHz	3.40 GHz	165 W	DDR4-2933
Intel® Xeon® Processor Gold 5318S	IceLake	QXRX	M1	36MB	11.2GT/s	24	2.10 GHz	3.40 GHz	165 W	DDR4-2933
Intel® Xeon® Processor Gold 5318N	IceLake	QXS4	M1	36MB	11.2GT/s	24	2.10 GHz	3.40 GHz	150 W	DDR4-2667
Intel® Xeon® Processor Gold 5317	IceLake	QXRM	M1	18MB	11.2GT/s	12	3.00 GHz	3.60 GHz	150 W	DDR4-2933
Intel® Xeon® Processor Gold 5315Y	IceLake	QXRR	M1	12MB	11.2GT/s	8	3.20 GHz	3.60 GHz	140 W	DDR4-2933
Intel® Xeon® Processor Silver 4316	IceLake	QXS5	M1	30MB	10.4GT/s	20	2.30 GHz	3.40 GHz	150 W	DDR4-2667
Intel® Xeon® Processor Silver 4314	IceLake	QXS8	M1	24MB	11.2GT/s	16	2.40 GHz	3.40 GHz	135 W	DDR4-2667
Intel® Xeon® Processor Silver 4310T	IceLake	QXRP	M1	15MB	11.2GT/s	10	2.30 GHz	3.40 GHz	105 W	DDR4-2667
Intel® Xeon® Processor Silver 4310	IceLake	QXRN	M1	18MB	10.4GT/s	12	2.10 GHz	3.30 GHz	120 W	DDR4-2667
Intel® Xeon® Processor Silver 4309Y	IceLake	QXRS	M1	12MB	11.2GT/s	8	2.80 GHz	3.60 GHz	105 W	DDR4-2667

Memory (Memory actually maximum frequency will follow memory controller's spec of CPU you used)

Product Name	Memory Type	Module Supplier	Size	Chip Brand	Rank	Voltage	Data Transfer Rate	Error Correction	CAS Latency	Pins
RDIMM										
M393A4K40DB2-CVFBQ	DDR4	Samsung	32GB	Samsung-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
M393A8G40AB2-CVFBY	DDR4	Samsung	64GB	Samsung-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
CT32G4RFD4293-2G9E2.001	DDR4	CRUCIAL	32GB	Micron	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
CT32G4RFD4293.36FE2	DDR4	CRUCIAL	32GB	Micron	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin

MTA36ASF4G72PZ.2G9E2TG	DDR4	Micron	32GB	Micron-Montage	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ.2G9E2VG	DDR4	Micron	32GB	Micron-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ.2G9E2UG	DDR4	Micron	32GB	Micron-Rambus	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA18ASF4G72PDZ-2G9E1TI	DDR4	Micron	32GB	Micron-Montage	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
HMAA8GR7MJR4N-WM T4	DDR4	SKhynix	64GB	SKhynix-Montage	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
KSM29RD4/32HDR	DDR4	Kingston	32GB	SKhynix-Rambus	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
NT32GA72D4NBX3P-IX	DDR4	Nanya	32GB	Nanya-Montage or IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
HMA84GR7DJR4N-XN T4	DDR4	SKhynix	32GB	SKhynix-Montage	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
HMAA8GR7CJR4N-XN T4	DDR4	SKhynix	64GB	SKhynix-Montage	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
HMAA8GR7CJR4N-XN TG	DDR4	SKhynix	64GB	SKhynix-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
HMAA8GR7CJR4N-XN T8	DDR4	SKhynix	64GB	SKhynix-Rambus	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
MTA18ASF2G72PZ-3G2R1UI	DDR4	Micron	16GB	Micron-Rambus	1Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
MTA18ASF4G72PDZ.3G2B2TI	DDR4	Micron	32GB	Micron-Montage	2Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
MTA36ASF4G72PZ-3G2R1UI	DDR4	Micron	32GB	Micron-Rambus	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A2K40EB3-CWEGQ	DDR4	Samsung	16GB	Samsung-Rambus	1Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4K40DB3-CWECQ	DDR4	Samsung	32GB	Samsung-Montage	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4K40DB3-CWEBQ	DDR4	Samsung	32GB	Samsung-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4K40DB3-CWEGQ	DDR4	Samsung	32GB	Samsung-Rambus	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4G40BB3-CWEGQ	DDR4	Samsung	32GB	Samsung-Rambus	1Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4K40EB3-CWEGQ	DDR4	Samsung	32GB	Samsung-Rambus	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin

M393A4K40EB3-CWECQ	DDR4	Samsung	32GB	Samsung-Montage	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4K40EB3-CWEBY	DDR4	Samsung	32GB	Samsung-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A8G40BB4-CWEBY	DDR4	Samsung	64GB	Samsung-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393AAG40M32-CAEBQ	DDR4	Samsung	128GB	Samsung	2S2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
KSM32RS8/16MER	DDR4	Kingston	16GB	Micron-Rambus	1Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
KSM32RS4/32MER	DDR4	Kingston	32GB	Micron-Rambus	1Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
AD4R3200716G22-BHYA	DDR4	ADATA	16GB	SKhynix-Montage	1Rx8	1.2v	3200MHz	ECC Registered	22	288-pin

LRDIMM

M386A8K40CM2-CVFBY	DDR4	Samsung	64GB	Samsung-IDT	4DRx4	1.2v	2933MHz	ECC Registered	21	288-pin
M386AAG40MMB-CVFC0	DDR4	Samsung	128GB	Samsung	4DRx4	1.2v	2933MHz	ECC Registered	21	288-pin
M386A8K40DM2-CWELQ	DDR4	Samsung	64GB	Samsung-IDT	4DRx4	1.2v	3200MHz	ECC Registered	22	288-pin

HDD (if the system build-in with RAID card ,please refer to RAID card QVL list)

Product Name	Type	Vendor	Form Factor	Format	Capacity	Interface Speed	Series	Cache	RPM	Encryption
--------------	------	--------	-------------	--------	----------	-----------------	--------	-------	-----	------------

Seagate Enterprise Capacity 2.5 HDD

ST2000NX0243	SATA	Seagate	2.5"	4Kn	2TB	6Gb/s	Exos 7E2000 (Enterprise Capacity V.3)	128MB	7200	N/A
--------------	------	---------	------	-----	-----	-------	--	-------	------	-----

SATA/SAS SSD

Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	FW	Note
--------------	------	--------	-------------	-----------	----------	-----------------	----	------

SATA SSD

MZ-7LH1T9NE 883 DCT Series	SSD	Samsung	2.5"	SATA	1.92TB	6Gb/s		
SSDSC2KG019T8 D3-S4610 Series	SSD	Intel	2.5"	SATA	1.92TB	6Gb/s		
SSDSC2KB019T8 D3-S4510 Series	SSD	Intel	2.5"	SATA	1.92TB	6Gb/s		

PCIe SSD

Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	Note
--------------	------	--------	-------------	-----------	----------	-----------------	------

PCIe SSD

SSDPEDKX040T701 P4500 Series PCIe Gen3 x4 4TB	PCIe	Intel	PCI-E 3.0	PCIe(NVMe)	4TB	PCIe Gen3 x4	
Samsung PM1725b MZPLL3T2HAJQ PCIe Gen3 x8 3.2TB	PCIe	Samsung	PCI-E 3.0	PCIe(NVMe)	3.2TB	PCIe Gen3 x8	

U.2

Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	Note
--------------	------	--------	-------------	-----------	----------	-----------------	------

U.2

SSDPF2KX038TZ D7-P5510 Series	U.2	Intel	2.5"	SFF8639(NVMe)	3.84TB	PCIe Gen4 x4	
SSDPE2KE032T801 P4610 Series	U.2	Intel	2.5"	SFF8639(NVMe)	3.2TB	PCIe Gen3 x4	
SSDPE2KX020T801 P4510 Series	U.2	Intel	2.5"	SFF8639(NVMe)	2TB	PCIe Gen3 x4	
MZWL3T2HAJQ PM1725b Series	U.2	Samsung	2.5"	SFF8639(NVMe)	3.2TB	PCIe Gen3 x4	
MZQLW1T9HMJP PM963 Series	U.2	Samsung	2.5"	SFF8639(NVMe)	1.92TB	PCIe Gen3 x4	
MZQL23T8HCLS PM9A3 Series	U.2	Samsung	2.5"	SFF8639(NVMe)	3.84TB	PCIe Gen4 x4	
MTFDHAL3T2TDR 9300 Max Series	U.2	Micron	2.5"	SFF8639(NVMe)	3.2TB	PCIe Gen3 x4	

U.3

KCM61RUL3T84 CM6-R Series	U.3	KIOXIA	2.5"	SFF8639(NVMe)	3.84TB	PCIe Gen4 x4			
---------------------------	-----	--------	------	---------------	--------	--------------	--	--	--

GPGPU Card (GPGPU server only)

Product Name	Processor Cores	Memory Bandwidth (GB/sec)	VRAM	OpenGL	Microsoft DirectX	Graphics Card Power (W)	NVIDIA SLI / AMD CrossFire Ready	Note
--------------	-----------------	---------------------------	------	--------	-------------------	-------------------------	----------------------------------	------

NVIDIA Tesla (<http://www.nvidia.com/object/tesla-supercomputing-solutions.html>)

A100-HGX 4-GPU Redstone (Ampere)	6912	1555 GB/s	40GB			1615 W		
----------------------------------	------	-----------	------	--	--	--------	--	--

LAN Cards

Product Name	Connector	System Interface Type	# of Ports	Data Rate	Note
--------------	-----------	-----------------------	------------	-----------	------

Intel_25GbE

Intel® Ethernet Network Adapter E810-XXVDA2 for OCP	SFP28	OC P PCIe Gen4 x8	Dual	25Gb/s per port	Support OCP 3.0
Intel® Ethernet Network Adapter XXV710-DA2	SFP28	PCIe Gen3 x8	Dual	25Gb/s per port	

Intel_100GbE

Intel® Ethernet Network Adapter E810-CQDA2 for OCP	QSFP28	OC P PCIe Gen4 x16	Dual	100Gb/s per port	Support OCP 3.0
Intel® Ethernet Network Adapter E810-CQDA2	QSFP28	PCIe Gen4 x16	Dual	100Gb/s per port	

Mellanox ConnectX

MCX631102AN-ADAT	SFP28	PCIe Gen4 x8	Dual	25Gb/s per port	ConnectX@-6 Dx without Crypto
MCX631432AN-ADAB	SFP28	OC P PCIe Gen4 x8	Dual	25Gb/s per port	ConnectX@-6 Lx without Crypto / Support OCP 3.0
MCX623105AN-CDAT	QSFP56	PCIe Gen4 x16	Single	100Gb/s per port	ConnectX@-6 Dx No Crypto, No Secure Boot
MCX623106AN-CDAT	QSFP56	PCIe Gen4 x16	Dual	100Gb/s per port	ConnectX@-6 Dx No Crypto, No Secure Boot
MCX623435AC-VDAB	QSFP56	OC P PCIe Gen4 x16	Single	200Gb/s per port	ConnectX@-6 Dx With Crypto1, With Secure Boot / Support OCP 3.0
MCX613106A-VDAT	QSFP56	PCIe Gen4 x16	Dual	200Gb/s per port	Mellanox ConnectX-6 EN
MCX565M-CDAB	QSFP28	OC P PCIe Gen4 x16	Single	100Gb/s per port	ConnectX@-5 Ex Multi-Host / Support OCP 3.0
MCX623432AN-ADAB	SFP28	OC P PCIe Gen4 x16	Dual	25Gb/s per port	ConnectX@-6 Dx No Crypto, No Secure Boot / Support OCP 3.0

Mellanox VPI Adapter Cards

MCX653436A-HDAI	QSFP56	OC P PCIe Gen4 x16	Dual	200Gb/s per port	Mellanox ConnectX-6 Ex VPI (InfiniBand) / OCP3.0
-----------------	--------	---------------------------	------	------------------	--

(Mellanox) NVIDIA BlueField-2 DPU Cards

QL45611HLCU	QSFP28	PCIe Gen3 x16	Single	100Gb/s per port	
-------------	--------	---------------	--------	------------------	--

USB Device

Product Name	Type	Vendor	Capacity	Note					
USB 3.0									
PURE CLASSIC X176B1FWBO75	HDD	Gigabyte	500G						
GoFlex STAA500305	HDD	Seagate	500G						
TOSHIBA CANVIO BASIC	HDD	Toshiba	500G						
NA317U+	Device	ineo							
SST-TS13	Device	Silver Stone							
S1-DS3-Plus	Device	CyberSLIM							
MB981U3-1S	Device	ICYDOCK							
i310-SB3(6G)	Device	STARDOM							