

**"R182-NA0" Qualification Vender List**

**Please contact FAE support for below orange blocks**

Intel CPU										
Product Name	Code Name	Q-Spec	Stepping	Cache	System Bus	# of Cores	Processor Base Frequency	Max Turbo Frequency	TDP	Memory Types
IceLake - Intel 3rd Generation Xeon Scalable Family										
Intel® Xeon® Processor Platinum 8380	IceLake	QXC0	D1	60MB	11.2GT/s	40	2.3 GHz	3.4 GHz	270W	DDR4-3200
Intel® Xeon® Processor Platinum 8368	IceLake	QWLL	D1	57MB	11.2GT/s	38	2.4 GHz	3.4 GHz	270W	DDR4-3200
Intel® Xeon® Processor Platinum 8360Y	IceLake	QXBZ	D1	54MB	11.2GT/s	36	2.4 GHz	3.5 GHz	250W	DDR4-3200
Intel® Xeon® Processor Platinum 8358P	IceLake	QXCM	D1	48MB	11.2GT/s	32	2.6 GHz	3.4 GHz	240W	DDR4-3200
Intel® Xeon® Processor Platinum 8352Y	IceLake	QWM3	D1	48MB	11.2GT/s	32	2.2 GHz	3.4 GHz	205W	DDR4-3200
Intel® Xeon® Processor Gold 6346	IceLake	QWMD	D1	36MB	11.2GT/s	16	3.1 GHz	3.6 GHz	205W	DDR4-3200
Intel® Xeon® Processor Gold 6338	IceLake	QWN3	D1	48MB	11.2GT/s	32	2.0 GHz	3.2 GHz	205W	DDR4-3200
Intel® Xeon® Processor Gold 6338N	IceLake	QWM6	D1	48MB	11.2GT/s	32	2.2 GHz	3.5 GHz	185W	DDR4-3200
Intel® Xeon® Processor Gold 6330	IceLake	QWMC	D1	42MB	11.2GT/s	28c	2.0 GHz	3.1 GHz	205W	DDR4-3200
Intel® Xeon® Processor Gold 6330N	IceLake	QWLP	D1	42MB	11.2GT/s	28	2.2 GHz	3.4 GHz	165W	DDR4-2667
Memory (Memory actually maximum frequency will follow memory controller's spec of CPU you used)										
Product Name	Memory Type	Module Supplier	Size	Chip Brand	Rank	Voltage	Data Transfer Rate	Error Correction	CAS Latency	Pins
RDIMM										
M393A2K43DB2-CVFBQ	DDR4	Samsung	16GB	Samsung-IDT	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
M393A8G40AB2-CVFBY	DDR4	Samsung	64GB	Samsung-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA9ASF2G72PZ-2G9E1UI	DDR4	Micron	16GB	Micron-Rambus	1Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
CT32G4RFD4293-2G9E2.001	DDR4	CRUCIAL	32GB	Micron	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
CT32G4RFD4293.36FE2	DDR4	CRUCIAL	32GB	Micron	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ.2G9E2TG	DDR4	Micron	32GB	Micron-Montage	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ.2G9E2VG	DDR4	Micron	32GB	Micron-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ.2G9E2UG	DDR4	Micron	32GB	Micron-Rambus	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
HMAA8GR7CJR4N-XN T4	DDR4	SKhynix	64GB	SKhynix-Montage	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
HMAA8GR7CJR4N-XN TG	DDR4	SKhynix	64GB	SKhynix-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
HMAA8GR7CJR4N-XN T8	DDR4	SKhynix	64GB	SKhynix-Rambus	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
MTA36ASF4G72PZ-3G2J3UI	DDR4	Micron	32GB	Micron-Rambus	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4K40DB3-CWECQ	DDR4	Samsung	32GB	Samsung-Montage	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4K40DB3-CWEBQ	DDR4	Samsung	32GB	Samsung-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin

M393A4K40DB3-CWEGQ	DDR4	Samsung	32GB	Samsung-Rambus	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A8G40AB2-CWEBQ	DDR4	Samsung	64GB	Samsung-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
KSM32RS4/32MER	DDR4	Kingston	32GB	Micron-Rambus	1Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
AD4R3200716G22-BHYA	DDR4	ADATA	16GB	SKhynix-Montage	1Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
LRDIMM										
M386A8K40CM2-CVFBY	DDR4	Samsung	64GB	Samsung-IDT	4DRx4	1.2v	2933MHz	ECC Registered	21	288-pin
M386A8K40DM2-CWELQ	DDR4	Samsung	64GB	Samsung-IDT	4DRx4	1.2v	3200MHz	ECC Registered	22	288-pin
<b>Seagate HDD (SAS HDD may need RAID Card support)</b>										
Product Name	Type	Vendor	Form Factor	Format	Capacity	Interface Speed	Series	Cache	RPM	Encryption
Seagate Enterprise Capacity 2.5 HDD										
ST2000NX0243	SATA	Seagate	2.5"	4Kn	2TB	6Gb/s	Exos 7E2000 (Enterprise Capacity V.3)	128MB	7200	N/A
<b>SATA/SAS SSD</b>										
Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	FW	Note		
SATA/SAS SSD										
MTFDDAK3T8TDS-1AW1ZABYY (5300 PRO)	SSD	Micron	2.5"	SATA	3.84TB	6Gb/s				
MTFDDAK1T9TDS-1AW1ZABYY (5300 PRO)	SSD	Micron	2.5"	SATA	1.92TB	6Gb/s				
MZ-7LH1T9NE 883 DCT Series	SSD	Samsung	2.5"	SATA	1.92TB	6Gb/s				
SSDSC2KG019T8 D3-S4610 Series	SSD	Intel	2.5"	SATA	1.92TB	6Gb/s				
SSDSC2KB019T8 D3-S4510 Series	SSD	Intel	2.5"	SATA	1.92TB	6Gb/s				
XA960LE10063	SSD	Seagate	2.5"	SATA	960GB	6Gb/s				
XA480LE10063	SSD	Seagate	2.5"	SATA	480GB	6Gb/s				
KHK61RSE960G	SSD	Toshiba	2.5"	SATA	960GB	6Gb/s				
<b>PCIe SSD</b>										
Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	Note			
PCIe SSD										
SSDPEDKX040T701 P4500 Series PCIe Gen3 x4 4TB	PCIe	Intel	PCI-E 3.0	PCIe(NVMe)	4TB	Gen3 x4				
<b>U.2</b>										
Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	Note			
U.2 (VROC support)										
SSDPE2KE032T801 P4610 Series	U.2	Intel	2.5"	SFF8639(NVMe)	3.2TB	Gen3 x4				
SSDPE2KX020T801 P4510 Series	U.2	Intel	2.5"	SFF8639(NVMe)	2TB	Gen3 x4				
<b>U.2</b>										
SSDPE2KE032T801 P4610 Series	U.2	Intel	2.5"	SFF8639(NVMe)	3.2TB	Gen3 x4				
SSDPE2KX020T801 P4510 Series	U.2	Intel	2.5"	SFF8639(NVMe)	2TB	Gen3 x4				
MZWLL3T2HAJQ PM1725b Series	U.2	Samsung	2.5"	SFF8639(NVMe)	3.2TB	Gen3 x4				
MTFDHAL3T2TCU 9200 Series	U.2	Micron	2.5"	SFF8639(NVMe)	3.2TB	Gen3 x4				
KCD51LUG960G CD5 Series	U.2	Toshiba	2.5"	SFF8639(NVMe)	960GB	Gen3 x4				
<b>U.3</b>										
KCM61RUL3T84 CM6-R Series	U.3	KIOXIA	2.5"	SFF8639(NVMe)	3.84TB	Gen4 x4				
<b>SATA DOM</b>										

Product Name	Type	Vendor	Capacity	Flash Type	Max. Channels	Max. Power Consumption	Note			
<b>SATA III</b>										
Innodisk SATADOM-SL 3ME4 DESSL-64GM41BC1SCB	Vertical	INNODISK	64GB	MLC	1	0.734 W				
Innodisk SATADOM-SL 3ME4 DESSL-A28M41BCADCB-D33	Vertical	INNODISK	128GB	MLC	1	1.02 W				
Innodisk SATADOM-ML 3ME4 DESML-64GM41BCADCB	Vertical	INNODISK	64GB	MLC	2	0.815 W				
Innodisk SATADOM-SH TYPE C 3ME4 DESSC-64GM41BC1SCB	Horizontal	INNODISK	64GB	MLC	1	0.626 W				
<b>RAID Cards</b>										
Model	RAID-on-Chip Controller	Host Bus Type	Internal Ports	Internal Connectors	External Ports	External Connectors	Data Transfer Rates	Note		
<b>GIGABYTE Storage Cards</b>										
CRA3338	LSI SAS 3008	PCIe- x8 Gen3 x8 bus	8	2 xMini-SAS HD for 8x SAS	-	-	12Gb/s ports			
CSA3548	LSI SAS 3008	PCIe- x8 Gen3 x8 bus	-	-	8	2 x external Mini-SAS HD SFF8644	12Gb/s ports			
CRA4448	LSI SAS 3108	PCIe- x8 Gen3 x8 bus	8	2 x internal Mini-SAS HD SFF8643	-	-	12Gb/s ports			
CRAO438	LSI SAS 3108	<b>DCP</b> PCIe- x8 Gen3 x8 bus	8	2 x SlimSAS ports	-	-	12Gb/s ports			
CRAO338	LSI SAS 3008	<b>DCP</b> PCIe- x8 Gen3 x8 bus	8	2 x SlimSAS ports	-	-	12Gb/s ports			
<b>LSI RAID Controller Cards</b>										
MegaRAID SAS 9460-16i	SAS3516 dual-core RAID-on-Chip (ROC)	x8 lane PCI Express® 3.1	8	4 x Mini-SAS HD SFF-8643	-	-	12Gb/s SAS 3.0			
<b>LSI Host Bus Adapters (HBAs)</b>										
LSI SAS 9400-16i	SAS3416	x8 lane PCI Express® 3.1	16	4 x Mini-SAS HD SFF-8643	-	-	12Gb/s SAS 3.0			
<b>Microsemi RAID Cards</b>										
SmartRAID 3154-16i	PM8236	8-Lane PCIe Gen3	16	4 x Internal, SFF-8643	-	-	12 Gb/s per port			
<b>Microsemi Host Bus Adapters</b>										
SmartHBA 2100-8i	PM8222	8-Lane PCIe Gen3	8	2 x Internal, SFF-8643	-	-	12 Gb/s per port			
<b>LAN Cards</b>										
Product Name	Connector	System Interface Type	# of Ports	Data Rate	Note					
<b>GIGABYTE LAN Cards</b>										
CLNO832	SFP+	<b>DCP</b> PCIe x8 Gen2 x8	Dual	10Gb/s per port	INTEL 82599ES Support OCP 2.0 type1					
CLNOQ42	SFP28	<b>DCP</b> PCIe x8 Gen3 x8	Dual	25Gb/s per port	Qlogic (Cavium) QL41401-A2G Support OCP 2.0					
CLNO222	RJ-45	<b>DCP</b> PCIe Gen3 x4	Dual	10Gb/s per port	INTEL X550-AT2 Support OCP 2.0 type1					
CLN4752	QSFP+	PCIe x8 Gen3 x8	Dual	40Gb/s per port	INTEL XL710					
CLN4224	RJ-45	PCIe x8 Gen3 x4	Quad	10Gb/s per port	INTEL X550-AT2					
CLN4M34	SFP28	PCIe Gen3 x16	Quad	10Gb/s per port	Mellanox ConnectX-4					
<b>Intel_10GbE</b>										
Intel® Ethernet Network Adapter X722-DA4	SFP+	PCIe v3.0 (8.0 GT/s)	Quad	10Gb/s per port						
<b>Intel_25GbE</b>										
Intel® Ethernet Network Adapter XXV710-DA2 for OCP	SFP28	<b>DCP</b> PCIe v3.0 (8.0 GT/s)	Dual	25Gb/s per port	Support OCP 2.0 type1					

Intel® Ethernet Network Adapter XXV710-DA2	SFP28	PCIe v3.0 (8.0 GT/s)	Dual	25Gb/s per port	
Intel_40GbE					
Intel® Ethernet Converged Network Adapter XL710-QDA2	QSFP+	PCIe v3.0 (8.0 GT/s)	Dual	40Gb/s per port	
Mellanox ConnectX					
MCX566A-CDAI	QSFP28	<b>DCP PCIe 4.0</b> x16	Dual	100Gb/s per port	Mellanox ConnectX-5 Ex EN / Support OCP 3.0
MCX516A-CDAT	QSFP28	<b>PCIe 4.0</b> x16	Dual	100Gb/s per port	Mellanox ConnectX-5 Ex EN
MCX516A-CCAT	QSFP28	PCIe Gen3 x16	Dual	100Gb/s per port	Mellanox ConnectX-5 EN
MCX515A-CCAT	QSFP28	PCIe Gen3 x16	Single	100Gb/s per port	Mellanox ConnectX-5 EN
MCX4421A-ACQN	SFP28	<b>DCP</b> PCIe Gen3 x8	Dual	25Gb/s per port	Mellanox ConnectX-4 Lx EN / Support OCP 2.0
MCX4121A-ACAT	SFP28	PCIe Gen3 x8	Dual	25Gb/s per port	Mellanox ConnectX-4 Lx EN
Mellanox VPI Adapter Cards					
MCX654106A-HCAT	QSFP56	PCIe 3.0 x16	Dual	200Gb/s per port	Mellanox ConnectX-6 Ex VPI (InfiniBand) PCIe3.0 x16 + PCIe3.0x16 aux. card Socket Direct
MCX653106A-HDAT	QSFP56	<b>PCIe 4.0</b> x16	Dual	200Gb/s per port	Mellanox ConnectX-6 Ex VPI (InfiniBand)
MCX653105A-ECAT	QSFP56	<b>PCIe 4.0</b> x16	Single	100Gb/s per port	Mellanox ConnectX-6 Ex VPI (InfiniBand)
MCX653106A-ECAT	QSFP56	<b>PCIe 4.0</b> x16	Dual	100Gb/s per port	Mellanox ConnectX-6 Ex VPI (InfiniBand)
MCX556A-EDAT	QSFP28	<b>PCIe 4.0</b> x16	Dual	100Gb/s per port	Mellanox ConnectX-5 Ex VPI (InfiniBand)
MCX555A-ECAT	QSFP28	PCIe 3.0 x16	Single	100Gb/s per port	Mellanox ConnectX-5 VPI (InfiniBand)
Qlogic LAN Adapters					
QL45611HLCU	QSFP28	PCIe x16 Gen3 x16	Single	100Gb/s per port	
QLE3442-RJ-CK	RJ-45	PCIe x8 Gen3 x8	Dual	10Gb/s per port	
Broadcom (Emulex) Ethernet Networking Adapters					
BCM957508-P2100G	QSFP56	<b>PCIe 4.0</b> x16	Dual	100Gb/s per port	BCM57508
BCM957414A4142CC	SFP28	PCIe 3.0 x8	Dual	25Gb/s per port	BCM57414
BCM957508-N2100G	QSFP56	<b>DCP PCIe 4.0</b>	Dual	100Gb/s per port	BCM57508 / Support <b>DCP 3.0</b>
BCM957504-N425G	SFP28	<b>DCP PCIe 4.0</b>	Quad	25Gb/s per port	BCM57504 / Support <b>DCP 3.0</b>
BCM957414M4142C	SFP28	<b>DCP</b> PCIe 3.0 x8	Dual	25Gb/s per port	BCM57414 / Support OCP 2.0 type1
BCM957416A4160C	RJ-45	PCIe 3.0 x8	Dual	10Gb/s per port	BCM5741 (P210TP)
Broadcom FC Host Bus Adapter					
LPe32002-M2	SFP+	PCIe 3.0 x8	Dual	32Gb/s per port	XE501 controller
LPe31002-M6	SFP+	PCIe Gen3 x8	Dual	16Gb/s per port	XE501 controller
<b>USB Device</b>					
Product Name	Type	Vendor	Capacity	Note	
USB 3.0					
PURE CLASSIC X176B1FWBO75	HDD	Gigabyte	500G		
GoFlex STAA500305	HDD	Seagate	500G		
TOSHIBA CANVIO BASIC	HDD	Toshiba	500G		
NA317U+	Device	ineo			

SST-TS13	Device	Silver Stone								
S1-DS3-Plus	Device	CyberSLIM								
MB981U3-1S	Device	ICYDOCK								
i310-SB3(6G)	Device	STARDOM								