

"R282-200" Qualification Vender List

Please contact FAE support for below orange blocks

Intel CPU										
Product Name	Code Name	Q-Spec	Stepping	Cache	System Bus	# of Cores	Processor Base Frequency	Max Turbo Frequency	TDP	Memory Types
Intel® Xeon® Processor Platinum 8380	IceLake	QXC0	D1	60MB	11.2GT/s	40	2.3 GHz	3.4 GHz	270W	DDR4-3200
Intel® Xeon® Processor Platinum 8368	IceLake	QWLL	D1	57MB	11.2GT/s	38	2.4 GHz	3.4 GHz	270W	DDR4-3200
Intel® Xeon® Processor Platinum 8368Q	IceLake	QXC1	D1	57MB	11.2GT/s	38	2.6 GHz	3.7 GHz	270W	DDR4-3200
Intel® Xeon® Processor Platinum 8360Y	IceLake	QXBZ	D1	54MB	11.2GT/s	36	2.4 GHz	3.5 GHz	250W	DDR4-3200
Intel® Xeon® Processor Platinum 8362	IceLake			48MB	11.2GT/s	32	2.80 GHz	3.60 GHz	265 W	DDR4-3200
Intel® Xeon® Processor Platinum 8358	IceLake	QWMU		48MB	11.2GT/s	32	2.6 GHz	3.4 GHz	250W	DDR4-3200
Intel® Xeon® Processor Platinum 8358P	IceLake	QXCM	D1	48MB	11.2GT/s	32	2.6 GHz	3.4 GHz	240W	DDR4-3200
Intel® Xeon® Processor Platinum 8352Y	IceLake	QWM3	D1	48MB	11.2GT/s	32	2.2 GHz	3.4 GHz	205W	DDR4-3200
Intel® Xeon® Processor Platinum 8352V	IceLake	SRK32	D2	54MB	11.2GT/s	36	2.1 GHz	3.5 GHz	195W	DDR4-2933
Intel® Xeon® Processor Platinum 8352M	IceLake	QXZ0	D2	48MB	11.2GT/s	32	2.30 GHz	3.50 GHz	185W	DDR4-3200
Intel® Xeon® Processor Gold 6346	IceLake	QWMD	D1	36MB	11.2GT/s	16	3.1 GHz	3.6 GHz	205W	DDR4-3200
Intel® Xeon® Processor Gold 6342	IceLake	QXRU	M1	36MB	11.2GT/s	24	2.80 GHz	3.50 GHz	230 W	DDR4-3200
Intel® Xeon® Processor Gold 6338	IceLake	QWN3	D1	48MB	11.2GT/s	32	2.0 GHz	3.2 GHz	205W	DDR4-3200
Intel® Xeon® Processor Gold 6338N	IceLake	QWM6	D1	48MB	11.2GT/s	32	2.2 GHz	3.5 GHz	185W	DDR4-2667
Intel® Xeon® Processor Gold 6338T	IceLake	QXS3	M1	36MB	11.2GT/s	24	2.10 GHz	3.40 GHz	165 W	DDR4-3200
Intel® Xeon® Processor Gold 6336Y	IceLake	QXRV	M1	36MB	11.2GT/s	24	2.40 GHz	3.60 GHz	185 W	DDR4-3200
Intel® Xeon® Processor Gold 6334	IceLake	QXRQ	M1	18MB	11.2GT/s	8	3.60 GHz	3.70 GHz	165 W	DDR4-3200
Intel® Xeon® Processor Gold 6330	IceLake	QWMC	D1	42MB	11.2GT/s	28c	2.0 GHz	3.1 GHz	205W	DDR4-2933
Intel® Xeon® Processor Gold 6330N	IceLake	QWLP	D1	42MB	11.2GT/s	28	2.2 GHz	3.4 GHz	165W	DDR4-2667
Intel® Xeon® Processor Gold 6326	IceLake	QXS7	M1	24MB	11.2GT/s	16	2.90 GHz	3.50 GHz	185 W	DDR4-3200
Intel® Xeon® Processor Gold 5320T	IceLake	QXS6	M1	30MB	11.2GT/s	20	2.30 GHz	3.50 GHz	150 W	DDR4-2993
Intel® Xeon® Processor Gold 5320	IceLake	QXRT	M1	39MB	11.2GT/s	26	2.20 GHz	3.40 GHz	185 W	DDR4-2933
Intel® Xeon® Processor Gold 5318Y	IceLake	QXS2	M1	36MB	11.2GT/s	24	2.10 GHz	3.40 GHz	165 W	DDR4-2933
Intel® Xeon® Processor Gold 5318S	IceLake	QXRX	M1	36MB	11.2GT/s	24	2.10 GHz	3.40 GHz	165 W	DDR4-2933
Intel® Xeon® Processor Gold 5318N	IceLake	QXS4	M1	36MB	11.2GT/s	24	2.10 GHz	3.40 GHz	150 W	DDR4-2667
Intel® Xeon® Processor Gold 5317	IceLake	QXRM	M1	18MB	11.2GT/s	12	3.00 GHz	3.60 GHz	150 W	DDR4-2933
Intel® Xeon® Processor Gold 5315Y	IceLake	QXRR	M1	12MB	11.2GT/s	8	3.20 GHz	3.60 GHz	140 W	DDR4-2933
Intel® Xeon® Processor Silver 4316	IceLake	QXS5	M1	30MB	10.4GT/s	20	2.30 GHz	3.40 GHz	150 W	DDR4-2667
Intel® Xeon® Processor Silver 4314	IceLake	QXS8	M1	24MB	11.2GT/s	16	2.40 GHz	3.40 GHz	135 W	DDR4-2667
Intel® Xeon® Processor Silver 4310T	IceLake	QXRP	M1	15MB	11.2GT/s	10	2.30 GHz	3.40 GHz	105 W	DDR4-2667
Intel® Xeon® Processor Silver 4310	IceLake	QXRN	M1	18MB	10.4GT/s	12	2.10 GHz	3.30 GHz	120 W	DDR4-2667
Intel® Xeon® Processor Silver 4309Y	IceLake	QXRS	M1	12MB	11.2GT/s	8	2.80 GHz	3.60 GHz	105 W	DDR4-2667

Memory (Memory actually maximum frequency will follow memory controller's spec of CPU you used)

Product Name	Memory Type	Module Supplier	Size	Chip Brand	Rank	Voltage	Data Transfer Rate	Error Correction	CAS Latency	Pins
RDIMM										
M393A2K43DB2-CVFBQ	DDR4	Samsung	16GB	Samsung-IDT	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
M393A8G40AB2-CVFBY	DDR4	Samsung	64GB	Samsung-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA9ASF2G72PZ-2G9E1UI	DDR4	Micron	16GB	Micron-Rambus	1Rx8	1.2v	2933MHz	ECC Registered	21	288-pin

CT32G4RFD4293-2G9E2.001	DDR4	CRUCIAL	32GB	Micron	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
CT32G4RFD4293.36FE2	DDR4	CRUCIAL	32GB	Micron	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ.2G9E2TG	DDR4	Micron	32GB	Micron-Montage	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ.2G9E2VG	DDR4	Micron	32GB	Micron-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ.2G9E2UG	DDR4	Micron	32GB	Micron-Rambus	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
HMAA8GR7CJR4N-XN T4	DDR4	SKhynix	64GB	SKhynix-Montage	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
HMAA8GR7CJR4N-XN TG	DDR4	SKhynix	64GB	SKhynix-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
HMAA8GR7CJR4N-XN T8	DDR4	SKhynix	64GB	SKhynix-Rambus	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
HMA82GR7DJR8N-XN T8	DDR4	SKhynix	16GB	SKhynix-Rambus	2Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
HMA82GR7DJR8N-XN TG	DDR4	SKhynix	16GB	SKhynix -IDT	2Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
HMAA8GR7CJR4N-XN T4	DDR4	SKhynix	64GB	SKhynix-Montage	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
HMAA8GR7CJR4N-XN TG	DDR4	SKhynix	64GB	SKhynix-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
HMAA8GR7CJR4N-XN T8	DDR4	SKhynix	64GB	SKhynix-Rambus	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
MTA9ASF2G72PZ-3G2E1TI	DDR4	Micron	16GB	Micron-Montage	1Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
MTA18ASF2G72PDZ-3G2J3UI	DDR4	Micron	16GB	Micron-Rambus	2Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4K40EB3-CWEGQ	DDR4	Samsung	32GB	Samsung-Rambus	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4K40EB3-CWECQ	DDR4	Samsung	32GB	Samsung-Montage	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4K40EB3-CWEBY	DDR4	Samsung	32GB	Samsung-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A8G40AB2-CWEBQ	DDR4	Samsung	64GB	Samsung-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
KSM32RS4/32MER	DDR4	Kingston	32GB	Micron-Rambus	1Rx4	1.2v	3200MHz	ECC Registered	22	288-pin

AD4R3200716G22-BHYA	DDR4	ADATA	16GB	SKhynix-Montage	1Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
LRDIMM										
M386A8K40CM2-CVFBY	DDR4	Samsung	64GB	Samsung-IDT	4DRx4	1.2v	2933MHz	ECC Registered	21	288-pin
M386A8K40DM2-CWELQ	DDR4	Samsung	64GB	Samsung-IDT	4DRx4	1.2v	3200MHz	ECC Registered	22	288-pin
HDD (If the system build-in with RAID card ,please refer to RAID card QVL list)										
Product Name	Type	Vendor	Form Factor	Format	Capacity	Interface Speed	Series	Cache	RPM	Encryption
Seagate Enterprise Capacity 2.5 HDD										
ST2000NX0243	SATA	Seagate	2.5"	4Kn	2TB	6Gb/s	Exos 7E2000 (Enterprise Capacity V.3)	128MB	7200	N/A
Toshiba Enterprise Hard Drives										
AL15SEB24EQ	SAS	Toshiba	2.5"	512e	2.4TB	12Gb/s	Performance	128MB	10500	N/A
SATA/SAS SSD										
Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	FW	Note		
SATA SSD										
MTFDDAK3T8TDS-1AW1ZABYY (5300 PRO)	SSD	Micron	2.5"	SATA	3.84TB	6Gb/s				
MTFDDAK1T9TDS-1AW1ZABYY (5300 PRO)	SSD	Micron	2.5"	SATA	1.92TB	6Gb/s				
MZ-7LH1T9NE 883 DCT Series	SSD	Samsung	2.5"	SATA	1.92TB	6Gb/s				
SSDSC2KG019T8 D3-S4610 Series	SSD	Intel	2.5"	SATA	1.92TB	6Gb/s				
SSDSC2KB019T8 D3-S4510 Series	SSD	Intel	2.5"	SATA	1.92TB	6Gb/s				
XA960LE10063	SSD	Seagate	2.5"	SATA	960GB	6Gb/s				
XA480LE10063	SSD	Seagate	2.5"	SATA	480GB	6Gb/s				
KHK61RSE960G	SSD	Toshiba	2.5"	SATA	960GB	6Gb/s				
PCIe SSD										
Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	Note			
PCIe SSD										
SSDPEDKX040T701 P4500 Series PCIe Gen3 x4 4TB	PCIe	Intel	PCI-E 3.0	PCIe(NVMe)	4TB	PCIe Gen3 x4				
Samsung PM1725b MZPLL3T2HAJQ PCIe Gen3 x8 3.2TB	PCIe	Samsung	PCI-E 3.0	PCIe(NVMe)	3.2TB	PCIe Gen3 x8				
SATA DOM										
Product Name	Type	Vendor	Capacity	Flash Type	Max. Channels	Max. Power Consumption	Note			
SATA III										
Innodisk SATADOM-SL 3ME4 DESSL-64GM41BC1SCB	Vertical	INNODISK	64GB	MLC	1	0.734 W				
Innodisk SATADOM-SL 3ME4 DESSL-A28M41BCADCB-D33	Vertical	INNODISK	128GB	MLC	1	1.02 W				
Innodisk SATADOM-ML 3ME4 DESML-64GM41BCADCB	Vertical	INNODISK	64GB	MLC	2	0.815 W				
Innodisk SATADOM-SH TYPE C 3ME4 DESSC-64GM41BC1SCB	Horizontal	INNODISK	64GB	MLC	1	0.626 W				
RAID Cards										
Product Name	RAID-on-Chip Controller	Host Bus Type	Internal Ports	Internal Connectors	External Ports	External Connectors	Data Transfer Rates	Note		
GIGABYTE Storage Cards										
CRA3338	LSI SAS 3008	PCIe Gen3 x8	8	2 x Mini-SAS HD SFF-8643	-	-	Up to 12Gb/s per port			
CSA3548	LSI SAS 3008	PCIe Gen3 x8	-	-	8	2 x Mini-SAS HD SFF-8644	Up to 12Gb/s per port			

CRA4448	LSI SAS 3108	PCIe Gen3 x8	8	2 x Mini-SAS HD SFF-8643	-	-	Up to 12Gb/s per port		
CRAO438	LSI SAS 3108	OCF PCIe Gen3 x8	8	2 x8 SlimSAS SFF-8654	-	-	Up to 12Gb/s per port		
CRAO338	LSI SAS 3008	OCF PCIe Gen3 x8	8	2 x8 SlimSAS SFF-8654	-	-	Up to 12Gb/s per port		
LSI RAID Controller Cards									
MegaRAID SAS 9460-16i without Tri-mode	SAS3516 dual-core RAID-on-Chip (ROC)	PCIe Gen3 x8	8	4 x Mini-SAS HD SFF-8643	-	-	Up to 12Gb/s per port		
MegaRAID 9560-16i without Tri-mode	SAS3916 Tri-Mode RAID-on-Chip (ROC)	PCIe Gen4 x8	16	2 x8 SlimSAS SFF-8654	-	-	Up to 12Gb/s per port		
LSI Host Bus Adapters (HBAs)									
LSI SAS 9500-16i without Tri-mode	SAS3816	PCIe Gen4 x8	16	2 x8 SlimSAS SFF-8654	-	-	Up to 12Gb/s per port		
Microsemi RAID Cards									
SmartRAID 3154-16i	PM8236	PCIe Gen3 x8	16	4 x Mini-SAS HD SFF-8643	-	-	Up to 12Gb/s per port		
Microsemi Host Bus Adapters									
SmartHBA 2100-8i	PM8222	PCIe Gen3 x8	8	2 x Mini-SAS HD SFF-8643	-	-	Up to 12Gb/s per port		
LAN Cards									
Product Name	Connector	System Interface Type	# of Ports	Data Rate	Note				
GIGABYTE LAN Cards									
CLNO832	SFP+	OCF PCIe Gen2 x8	Dual	10Gb/s per port	INTEL 82599ES Support OCP 2.0 type1				
CLNOQ42	SFP28	OCF PCIe Gen3 x8	Dual	25Gb/s per port	Qlogic (Cavium) QL41401-A2G Support OCP 2.0				
CLNO222	RJ-45	OCF PCIe Gen3 x4	Dual	10Gb/s per port	INTEL X550-AT2 Support OCP 2.0 type1				
CLN4752	QSFP+	PCIe Gen3 x8	Dual	40Gb/s per port	INTEL XL710				
CLN4224	RJ-45	PCIe Gen3 x4	Quad	10Gb/s per port	INTEL X550-AT2				
CLN4M34	SFP28	PCIe Gen3 x16	Quad	10Gb/s per port	Mellanox ConnectX-4				
Intel_10GbE									
Intel® Ethernet Network Adapter X722-DA4	SFP+	PCIe Gen3 x8	Quad	10Gb/s per port					
Intel_25GbE									
Intel® Ethernet Network Adapter XXV710-DA2 for OCP	SFP28	OCF PCIe Gen3 x8	Dual	25Gb/s per port	Support OCP 2.0 type1				
Intel® Ethernet Network Adapter XXV710-DA2	SFP28	PCIe Gen3 x8	Dual	25Gb/s per port					
Intel_40GbE									
Intel® Ethernet Converged Network Adapter XL710-QDA2	QSFP+	PCIe Gen3 x8	Dual	40Gb/s per port					
Intel_100GbE									
Intel® Ethernet Network Adapter E810-CQDA2	QSFP28	PCIe Gen4 x16	Dual	100Gb/s per port					
Mellanox ConnectX									
MCX565M-CDAB	QSFP28	OCF PCIe Gen4 x16	Single	100Gb/s per port	ConnectX@-5 Ex Multi-Host / Support OCP 3.0				
MCX623432AN-ADAB	SFP28	OCF PCIe Gen4 x16	Dual	25Gb/s per port	ConnectX@-6 Dx No Crypto, No Secure Boot / Support OCP 3.0				
MCX566A-CDAI	QSFP28	OCF PCIe Gen4 x16	Dual	100Gb/s per port	Mellanox ConnectX-5 Ex EN / Support OCP 3.0				
MCX516A-CDAT	QSFP28	PCIe Gen4 x16	Dual	100Gb/s per port	Mellanox ConnectX-5 Ex EN				

MCX516A-CCAT	QSFP28	PCIe Gen3 x16	Dual	100Gb/s per port	Mellanox ConnectX-5 EN
MCX515A-CCAT	QSFP28	PCIe Gen3 x16	Single	100Gb/s per port	Mellanox ConnectX-5 EN
MCX4121A-ACAT	SFP28	PCIe Gen3 x8	Dual	25Gb/s per port	Mellanox ConnectX-4 Lx EN
Mellanox VPI Adapter Cards					
MCX654106A-HCAT	QSFP56	PCIe Gen3 x16	Dual	200Gb/s per port	Mellanox ConnectX-6 Ex VPI (InfiniBand) PCIe3.0 x16 + PCIe3.0x16 aux. card Socket Direct
MCX653106A-HDAT	QSFP56	PCIe Gen4 x16	Dual	200Gb/s per port	Mellanox ConnectX-6 Ex VPI (InfiniBand)
MCX653436A-HDAI	QSFP56	OC P PCIe Gen4 x16	Dual	200Gb/s per port	Mellanox ConnectX-6 Ex VPI (InfiniBand) / OCP3.0
MCX653105A-ECAT	QSFP56	PCIe Gen4 x16	Single	100Gb/s per port	Mellanox ConnectX-6 Ex VPI (InfiniBand)
QL45611HLCU	QSFP28	PCIe Gen3 x16	Single	100Gb/s per port	
QLE3442-RJ-CK	RJ-45	PCIe Gen3 x8	Dual	10Gb/s per port	
Broadcom (Emulex) Ethernet Networking Adapters					
BCM957508-P2100G	QSFP56	PCIe Gen4 x16	Dual	100Gb/s per port	BCM57508
BCM957414A4142CC	SFP28	PCIe Gen3 x8	Dual	25Gb/s per port	BCM57414
BCM957508-N2100G	QSFP56	OC P PCIe 4.0	Dual	100Gb/s per port	BCM57508 / Support OC P 3.0
BCM957414M4142C	SFP28	OC P PCIe Gen3 x8	Dual	25Gb/s per port	BCM57414 / Support OCP 2.0 type1
Broadcom FC Host Bus Adapter					
LPe32002-M2	SFP+	PCIe Gen3 x8	Dual	32Gb/s per port	XE501 controller
LPe31002-M6	SFP+	PCIe Gen3 x8	Dual	16Gb/s per port	XE501 controller
USB Device					
Product Name	Type	Vendor	Capacity	Note	
USB 3.0					
PURE CLASSIC X176B1FWBO75	HDD	Gigabyte	500G		
GoFlex STAA500305	HDD	Seagate	500G		
TOSHIBA CANVIO BASIC	HDD	Toshiba	500G		
NA317U+	Device	ineo			
SST-TS13	Device	Silver Stone			
S1-DS3-Plus	Device	CyberSLIM			
MB981U3-1S	Device	ICYDOCK			
i310-SB3(6G)	Device	STARDOM			