

"G482-Z54" Qualification Vender List

Please contact FAE support for below orange blocks

AMD CPU										
Product Name	Code Name	Package	Stepping	L3 Cache	# of Cores / Threads	Processor Base Freq (GHz)	Processor Boost Max Freq (GHz)	Default TDP	cTDP Min / cDTP Max	Memory Types
AMD 7H12 100-000000055	ROME	SP3	PD	256MB	64 / 128	2.60	3.40	280W	225W/280W	DDR4-3200
AMD 7F72 100-000000141	ROME	SP3	PD	192MB	24 / 48	3.20	3.70	240W	225W/240W	DDR4-3200
AMD 7F52 100-000000140	ROME	SP3	PD	256MB	16 / 32	3.50	3.90	240W	225W/240W	DDR4-3200
AMD 7F32 100-000000139	ROME	SP3	B0 PR	128MB	8 / 16	3.70	3.90	180W	165W/200W	DDR4-3200
AMD 7742 100-000000053	ROME	SP3	B0 PR	256MB	64 / 128	2.25	3.40	225W	225W/240W	DDR4-3200
AMD 7702 100-000000038	ROME	SP3	B0 PR	256MB	64 / 128	2.00	3.35	200W	165W/200W	DDR4-3200
AMD 7662 100-000000137	ROME	SP3	PD	256MB	64 / 128	2.00	3.30	225W	225W/240W	DDR4-3200
AMD 7642 100-000000074	ROME	SP3	B0 PR	192MB	48 / 96	2.30	3.40	225W	225W/240W	DDR4-3200
AMD 7552 100-000000076	ROME	SP3	B0 PR	192MB	48 / 96	2.20	3.30	200W	165W/200W	DDR4-3200
AMD 7542 100-000000075	ROME	SP3	B0 PR	128MB	32 / 64	2.90	3.40	225W	225W/240W	DDR4-3200
AMD 7532 100-000000136	ROME	SP3	PD	256MB	32 / 64	2.40	3.30	200W	180W/200W	DDR4-3200
AMD 7502 100-000000054	ROME	SP3	B0 PR	128MB	32 / 64	2.50	3.35	180W	165W/200W	DDR4-3200
AMD 7452 100-000000057	ROME	SP3	B0 PR	128MB	32 / 64	2.35	3.35	155W	155W/180W	DDR4-3200
AMD 7402 100-000000046	ROME	SP3	B0 PR	128MB	24 / 48	2.80	3.35	180W	165W/200W	DDR4-3200
AMD 7352 100-000000077	ROME	SP3	B0 PR	128MB	24 / 48	2.30	3.20	155W	155W/180W	DDR4-3200
AMD 7302 100-000000043	ROME	SP3	B0 PR	128MB	16 / 32	3.00	3.30	155W	155W/180W	DDR4-3200
AMD 7282 100-000000078	ROME	SP3	B0 PR	64MB	16 / 32	2.80	3.20	120W	120W/150W	DDR4-2666
AMD 7272 100-000000079	ROME	SP3	PD	64MB	12 / 24	2.90	3.20	120W	120W/150W	DDR4-2666
AMD 7262 100-000000041	ROME	SP3	B0 PR	128MB	8 / 16	3.20	3.40	155W	155W/180W	DDR4-3200
AMD 7252 100-000000080	ROME	SP3	PD	64MB	8 / 16	3.10	3.20	120W	120W/150W	DDR4-2666

Memory (Memory actually maximum frequency will follow memory controller's spec of CPU you used)

Product Name	Memory Type	Module Supplier	Size	Chip Brand	Rank	Voltage	Data Transfer Rate	Error Correction	CAS Latency	Pins
RDIMM										
TR432G26D419-VKA	DDR4	V-color	32GB	Skhynix-Inphi	2Rx4	1.2v	2666MHz	ECC Registered	19	288-pin
M393A2K43DB2-CVFBQ	DDR4	Samsung	16GB	Samsung-IDT	2Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
M393A8G40AB2-CVFBY	DDR4	Samsung	64GB	Samsung-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA9ASF2G72PZ-2G9E1UI	DDR4	Micron	16GB	Micron-Rambus	1Rx8	1.2v	2933MHz	ECC Registered	21	288-pin
CT32G4RFD4293-2G9E2.001	DDR4	CRUCIAL	32GB	Micron	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
CT32G4RFD4293.36FE2	DDR4	CRUCIAL	32GB	Micron	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ.2G9E2TG	DDR4	Micron	32GB	Micron-Montage	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ.2G9E2VG	DDR4	Micron	32GB	Micron-IDT	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
MTA36ASF4G72PZ.2G9E2UG	DDR4	Micron	32GB	Micron-Rambus	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin

HMAA8GR7MJR4N-WM T4	DDR4	SKhynix	64GB	SKhynix-Montage	2Rx4	1.2v	2933MHz	ECC Registered	21	288-pin
HMA84GR7DJR4N-XN T4	DDR4	SKhynix	32GB	SKhynix-Montage	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
HMAA8GR7AJR4N-XN TG	DDR4	SKhynix	64GB	SKhynix-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
CT16G4RFD832A-3G2E1.001	DDR4	Crucial	16GB	Micron-Rambus	2Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
MTA18ASF2G72PDZ-3G2E1UK	DDR4	Micron	16GB	Micron-Rambus	2Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
MTA9ASF2G72PZ-3G2E1TI	DDR4	Micron	16GB	Micron-Montage	1Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
MTA18ASF2G72PZ-3G2E2TI	DDR4	Micron	16GB	Micron-Montage	1Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
MTA18ASF2G72PDZ-3G2J3UI	DDR4	Micron	16GB	Micron-Rambus	2Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
MTA18ASF4G72PDZ.3G2B2TI	DDR4	Micron	32GB	Micron-Montage	2Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
MTA36ASF4G72PZ-3G2J3UI	DDR4	Micron	32GB	Micron-Rambus	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
MTA18ASF4G72PDZ-3G2E1UI	DDR4	Micron	32GB	Micron-Rambus	2Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
MTA36ASF8G72PZ-3G2E1VI	DDR4	Micron	64GB	Micron-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A2K40DB3-CWEGQ	DDR4	Samsung	16GB	Samsung-Rambus	1Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A2K40DB3-CWEBQ	DDR4	Samsung	16GB	Samsung-IDT	1Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A2K40DB3-CWECQ	DDR4	Samsung	16GB	Samsung-	1Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4K40DB3-CWECQ	DDR4	Samsung	32GB	Samsung-Montage	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4K40DB3-CWEBQ	DDR4	Samsung	32GB	Samsung-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A4K40DB3-CWEGQ	DDR4	Samsung	32GB	Samsung-Rambus	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393A8G40AB2-CWEBQ	DDR4	Samsung	64GB	Samsung-IDT	2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
M393AAG40M32-CAEBQ	DDR4	Samsung	128GB	Samsung	2S2Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
TR416G32S422-XNC	DDR4	V-color	16GB	SKhynix-Rambus	1Rx4	1.2v	3200MHz	ECC Registered	22	288-pin
AD4R3200316G22-BSSC	DDR4	ADATA	16GB	Samsung-IDT	2Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
AD4R3200716G22-BHYA	DDR4	ADATA	16GB	SKhynix-Montage	1Rx8	1.2v	3200MHz	ECC Registered	22	288-pin
LRDIMM										
HMAA8GL7AMR4N-VKTF	DDR4	SKhynix	64GB	SKhynix	4DRx4	1.2v	2666MHz	ECC Registered	17	288-pin
M386A8K40CM2-CVFBY	DDR4	Samsung	64GB	Samsung-IDT	4DRx4	1.2v	2933MHz	ECC Registered	21	288-pin
M386A8K40DM2-CWELQ	DDR4	Samsung	64GB	Samsung-IDT	4DRx4	1.2v	3200MHz	ECC Registered	22	288-pin
Seagate HDD (SAS HDD may need RAID Card support)										
Product Name	Type	Vendor	Form Factor	Format	Capacity	Interface Speed	Series	Cache	RPM	Encryption
Seagate Enterprise Capacity 2.5 HDD										

ST2000NX0243	SATA	Seagate	2.5"	4Kn	2TB	6Gb/s	Exos 7E2000 (Enterprise Capacity V.3)	128MB	7200	N/A
SATA/SAS SSD										
Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	FW	Note		
SATA/SAS SSD										
MTFDDAK3T8TDS-1AW1ZABYY (5300 PRO)	SSD	Micron	2.5"	SATA	3.84TB	6Gb/s				
MTFDDAK1T9TDS-1AW1ZABYY (5300 PRO)	SSD	Micron	2.5"	SATA	1.92TB	6Gb/s				
MZ-7LH1T9NE 883 DCT Series	SSD	Samsung	2.5"	SATA	1.92TB	6Gb/s				
SSDSC2KG019T8 D3-S4610 Series	SSD	Intel	2.5"	SATA	1.92TB	6Gb/s				
SSDSC2KB019T8 D3-S4510 Series	SSD	Intel	2.5"	SATA	1.92TB	6Gb/s				
KHK61RSE960G	SSD	Toshiba	2.5"	SATA	960GB	6Gb/s				

PCIe SSD										
Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	Note			
PCIe SSD										
SSDPEDKX040T701 P4500 Series PCIe Gen3 x4 4TB	PCIe	Intel	PCI-E 3.0	PCIe(NVMe)	4TB	Gen3 x4				
Samsung PM1725b MZPLL3T2HAJQ PCIe Gen3 x8 3.2TB	PCIe	Samsung	PCI-E 3.0	PCIe(NVMe)	3.2TB	Gen3 x8				
U.2										
Product Name	Type	Vendor	Form Factor	Interface	Capacity	Interface Speed	Note			
U.2										
SSDPE2KE032T801 P4610 Series	U.2	Intel	2.5"	SFF8639(NVMe)	3.2TB	Gen3 x4				
SSDPE2KX020T801 P4510 Series	U.2	Intel	2.5"	SFF8639(NVMe)	2TB	Gen3 x4				
MZWLL3T2HAJQ PM1725b Series	U.2	Samsung	2.5"	SFF8639(NVMe)	3.2TB	Gen3 x4				
MZQLW1T9HMJP PM963 Series	U.2	Samsung	2.5"	SFF8639(NVMe)	1.92TB	Gen3 x4				
MTFDHAL3T2TCU 9200 Series	U.2	Micron	2.5"	SFF8639(NVMe)	3.2TB	Gen3 x4				
GPGPU Card (GPGPU server only)										
Product Name	Processor Cores	Memory Bandwidth (GB/sec)	VRAM	OpenGL	Microsoft DirectX	Graphics Card Power (W)	NVIDIA SLI / AMD CrossFire Ready	Note		
NVIDIA Tesla (http://www.nvidia.com/object/tesla-supercomputing-solutions.html)										
A100 (Ampere)	6912	1555 GB/s	40GB			250 W				
RTX8000 Passive (Turing)	4608	624 GB/s	48GB			250 W				
AMD Radeon Instinct										
MI50 (Vega20) 32GB	3840	1024GB/s	32GB			300 W				
LAN Cards										
Product Name	Connector	System Interface Type	# of Ports	Data Rate	Note					
GIGABYTE LAN Cards										
CLN4752	QSFP+	PCIe x8 Gen3 x8	Dual	40Gb/s per port	INTEL XL710 Intel_10GbE					
Intel® Ethernet Network Adapter X722-DA4	SFP+	PCIe v3.0 (8.0 GT/s)	Quad	10Gb/s per port	Intel_25GbE					
Intel® Ethernet Network Adapter XXV710-DA2	SFP28	PCIe v3.0 (8.0 GT/s)	Dual	25Gb/s per port	Intel_40GbE					
Intel® Ethernet Converged Network Adapter XL710-QDA2	QSFP+	PCIe v3.0 (8.0 GT/s)	Dual	40Gb/s per port	Mellanox ConnectX					
MCX516A-CDAT	QSFP28	PCIe 4.0 x16	Dual	100Gb/s per port	Mellanox ConnectX-5 Ex EN					
MCX516A-CCAT	QSFP28	PCIe Gen3 x16	Dual	100Gb/s per port	Mellanox ConnectX-5 EN					
MCX515A-CCAT	QSFP28	PCIe Gen3 x16	Single	100Gb/s per port	Mellanox ConnectX-5 EN					
MCX4121A-ACAT	SFP28	PCIe Gen3 x8	Dual	25Gb/s per port	Mellanox ConnectX-4 Lx EN					
Mellanox VPI Adapter Cards										
MCX654106A-HCAT	QSFP56	PCIe 3.0 x16	Dual	200Gb/s per port	Mellanox ConnectX-6 Ex VPI (InfiniBand) PCIe3.0 x16 + PCIe3.0x16 aux. card Socket Direct					
MCX653106A-HDAT	QSFP56	PCIe 4.0 x16	Dual	200Gb/s per port	Mellanox ConnectX-6 Ex VPI (InfiniBand)					
MCX653105A-ECAT	QSFP56	PCIe 4.0 x16	Single	100Gb/s per port	Mellanox ConnectX-6 Ex VPI (InfiniBand)					
MCX555A-ECAT	QSFP28	PCIe 3.0 x16	Single	100Gb/s per port	Mellanox ConnectX-5 VPI (InfiniBand)					
Qlogic LAN Adapters										
QL45611HLCU	QSFP28	PCIe x16 Gen3 x16	Single	100Gb/s per port						
QLE3442-RJ-CK	RJ-45	PCIe x8 Gen3 x8	Dual	10Gb/s per port						

Broadcom (Emulex) Ethernet Networking Adapters					
BCM957508-P2100G	QSFP56	PCIe 4.0 x16	Dual	100Gb/s per port	BCM57508
BCM957414A4142CC	SFP28	PCIe 3.0 x8	Dual	25Gb/s per port	BCM57414
BCM957416A4160C	RJ-45	PCIe 3.0 x8	Dual	10Gb/s per port	BCM5741 (P210TP)
USB Device					
Product Name	Type	Vendor	Capacity	Note	
USB 3.0					
PURE CLASSIC X176B1FWBO75	HDD	Gigabyte	500G		
NA317U+	Device	ineo			
S1-DS3-Plus	Device	CyberSLIM			
MB981U3-1S	Device	ICYDOCK			
i310-SB3(6G)	Device	STARDOM			